

CIR597X

smeg 90cm topmount gas cooktop



finish	satin stainless steel, cast-iron trivets (3) & burner caps
actual size	885mmW x 500mmD
installation	built-in one-piece hob
cutout	844mmW x 482mmD x 30mmH
capacity	44.3mj/hour max over five-six burners <ul style="list-style-type: none"> <li>• ultra-rapid inner, 3.5 mj.hr max</li> <li>• ultra-rapid outer, 11.5mj/hr max</li> <li>• combined 15.0mj/hr max</li> <li>• large rapid burner, 12.0 mj/hr max</li> <li>• 2x semi-rapid burners, 6.0mj/hr max each</li> <li>• 1x auxiliary burner, 4.8 mj/hr max</li> </ul>
ignition	automatic electronic
safety	flame failure device (FFD) fitted to each burner
gas input	set for natural gas — regulator supplied adaptable for ULPG — no regulator required
accessories	3 cast-iron trivets, pot rest, wok stand
options	cast-iron griddle plates — <ul style="list-style-type: none"> <li>• rectangular, 36cm x 21.5cm, code 9379</li> <li>• luxury 46cm x 24cm (BB3679)</li> </ul>
warranty	two years parts and labour

### SPACIOUS DESIGN

When space is not restrictive, this wide 90cm hob offers five burners ergonomically positioned for maximum benefit, with the possibility of several styles of cooking at the one time.

Also, cooked or yet to be cooked foods in their utensils are neatly contained within one safe area instead of occupying otherwise precious bench preparation or serving areas.

### ULTRA-RAPID DUAL BURNER

Conveniently and ergonomically positioned on the left, this versatile burner, while being designed for perfect wok cooking, also suits the larger stock pots, saucepans and griddles.

### AUXILIARY BURNERS

Perfectly situated, centre forward, this small burner enables a very low flame for the gentle simmer required for sauce reductions and low heat cooking and warming. A second auxiliary burner, capable of even lower heat simmering, is the separately controlled burner within the ultra-rapid dual control burner (wok).

### ELECTRONIC IGNITION

The cooktop is connected with a power cord of 1.3 metre length to be plugged into a GPO located according to installation needs below the benchline. This supplies a continuous stored charge to spark the gas supply to the individual burner of your choice. Simply depress and turn the control of the desired cooking zone for flame ignition.

### LOW MAINTENANCE

The seamless hob design allows for easy wipe-over cleaning and generous catchment of spills and accidental boilovers. The control knobs, also, are removable for cleaning access. Trivets, burner assemblies and wok stand can be washed in warm soapy water.

### INSTALLATION

With only a 30mm displacement into the benchtop, the cooktop allows for easy installation underbench of either oven, cupboards or drawers.

### CANALI DESIGN

The CIR597XS cooktop fits within a large and comprehensive range of Smeg appliances with complementing aesthetics. The architectural detail of Guido Canali makes possible the matching appliances, including the dishwasher.

### FLAME FAILURE

A flame failure device, FFD, with rapid ignition is fitted to each burner. The FFD ensures that should a flame be extinguished accidentally — the gas supply to the specific burner(s) is stopped. For absolute safety, the burner(s) can only be reignited by physically resetting the control knob(s) to the OFF position and then following normal ignition procedure.

CIR597X

smeg 90cm topmount gas cooktop

<b>overall height</b>	100mm
<b>above bench height</b>	65mm, includes control knobs
<b>below bench height</b>	35mm
<b>width</b>	885mm
<b>depth</b>	500mm
<b>packaged dimensions</b>	980mm x 650mm x 160mm = 0.11m <sup>3</sup>
<b>net weight</b>	20.5kg
<b>gross weight</b>	21.9kg
<b>capacity</b>	44.3mj/hour max over five-six burners <ul style="list-style-type: none"> <li>• ultra-rapid inner, 3.5 mj/hr max</li> <li>• ultra-rapid outer, 11.5mj/hr max</li> <li>• combined 15.0mj/hr max</li> <li>• large rapid burner, 12.0 mj/hr max</li> <li>• 2x semi-rapid burners, 6.0mj/hr max each</li> <li>• 1x auxiliary burner, 4.8 mj/hr max</li> </ul>
<b>NB</b>	SFFD, super flame failure device, fitted to each burner
<b>gas supply</b>	<ul style="list-style-type: none"> <li>• fitted for natural gas regulator — supplied</li> <li>• adaptable for ULPG — no regulator required</li> <li>• ½" BSP gas inlet connection</li> <li>• gas connection located below right-hand rear corner</li> </ul>
<b>ignition</b>	automatic electronic, 1.3 metre length power cord with 3-pin 10 plug for direct plugging to a 10 amp GPO
<b>supplied</b>	clips, seal, instructions for installation, operation, maintenance

**NB drawings are not to scale — they are to assist only**

