SIEMENS

iQ700 SX678X01TA stainless steel finish fully-integrated 60 cm tallTUB Dishwasher





















- \checkmark timeLight projects the status of the dishwasher and time remaining onto any floor surface
- ✓ varioSpeed: Up to 50% faster wash programs without sacrificing
 wash and drying results
- ✓ emotionLight bathes the dishwasher interior in a cool blue light

Feature

Technical Data

Water consumption (I): 12.0 Built-in / Free-standing: Built-in

Height of removable worktop (mm): 865

Required niche size for installation (HxWxD) : 865-925 x 600 x 550

Depth with open door 90 degree (mm): 1200

Adjustable feet : Yes - front only Maximum adjustability feet (mm) : 60

Net weight (kg): 48.0 Gross weight (kg): 51.0 Connection Rating (W): 2400

Current (A) : 10 Voltage (V) : 220-240 Frequency (Hz) : 50; 60

Length electrical supply cord (cm): 175

Plug type : AU plug

Length inlet hose (cm): 165 Length outlet hose (cm): 190 EAN code: 4242003694473 Number of place settings: 15 Energy consumption (kWh): 0.55 Reference programme: Eco

Total cycle time of reference programme (min): 160

Installation typology: Full-integrated



Optional accessories

SZ73300 Wineglass-Tray

SZ73001 Silver polishing cassette

SZ72010 inlet and outlet hose extention 2 m



iQ700 SX678X01TA stainless steel finish fully-integrated 60 cm tallTUB Dishwasher

Capacity

• 15 international place settings

Consumption rates

- 4.5 Star energy rating, 5 Star WELS water rating
- 12 litres water consumption per wash and 205kWh energy consumption, based on Eco 45°C program

- fully-integrated tallTUB Dishwasher 60 cm wide
- stainless steel finish
- stainless steel interior tub
- servo lock for effortless door closing
- SoftTouch buttons
- integrated control buttons at the top of the door panel

Wash Programs and Options

• 8 programs:

Auto 35-45°C

Auto 45-65°C Auto 65-75°C

Eco 45°C

Night Program 50°C

Glass 40°C

Ouick wash 45°C

Pre-Rinse

• 5 special options:

halfLoad Plus: For half loads, reduces energy, water & time

varioSpeed: Up to 50% faster wash time

intensiveZone: Powerful cleaning in the bottom basket hygienePlus: Removes bacteria from utensils & crockery shine & dry: Unique energy efficient Zeolith® drying cycle

Performance

- Zeolith® Drying Technology unique ground-breaking technology absorbs water molecules to dry dishes quicker with ultimate energy efficiency
- advanced 3 stage self-cleaning filter system
- dosageAssist detergent system
- iQdrive: The quietest, fastest, & most durable brushless motor ever built by Siemens
- hydroSensor: Automatic water turbidity detection loadSensor: Automatic water level optimisation
- automatic detergent aware system
- hydroDry hygienic drying
- alternating spray technique
- 5 spray levels for complete coverage

Flexibility

- varioDrawer Pro: Third loading level for cutlery & utensils
- varioFlex Pro basket system with blue coloured touchpoints
- 6 foldable plate racks in top basket
- 8 foldable plate racks in bottom basket
- 2 foldable cup shelves in top basket
- 2 foldable cup shelves in bottom basket
- rackMatic Plus: 3 stage height-adjustable upper basket
- variable position cutlery basket
- tall glass/champagne glass racks
- large item spray head vapor barrier plate

Convenience

- superSilence: Operates at a low noise level of 42dB
- Night Program operates at an even lower noise level of 40 dB
- emotionLight: Bathes your sparkling clean glassware in a cool blue illumination when you open the door
- TimeLight™: Projects wash status and remaining time onto the
- TFT Display in full colour on inner door
- Audible signal at end of program
- Time delay start (1-24 hours)
- Electronic rinse aid/refill indicator

Safety

- hydroSafe anti-flood protection
- Child door lock
- 5 year warranty

Dimensions

• 865-925 mm x 598 mm x 550 mm



iQ700 SX678X01TA stainless steel finish fully-integrated 60 cm tallTUB Dishwasher

Dimensioned drawings 1.2 m (3.4 m) 550 /- 865-925 - /-705-775 -// min. 90 max. 220 100 measurements in mm 600 598 min. 550 89] min. 90 max. 220 measurements in mm 550 598 865-925* min. 90 max. 220* 100 ** Stainless steel fascia up to max. 143mm * Because of height-adjustable screw feet: when appliance height is 865, base height is 90-160mm when appliance height is 925, base height is 150-220mm Measurements Measurements in mm