



# HYDROTAP G5 CS ELITE CHROME



CHILLED



SPARKLING

FILTERED

## Order Code H54787Z00AU

Zip HydroTap Design Range Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



|                    |             |
|--------------------|-------------|
| Manufacturing Code | H54787Z00AU |
| Capacity           | Residential |

|                           |                                                                                |
|---------------------------|--------------------------------------------------------------------------------|
| Tap                       | Zip HydroTap Design Range ELITE Tap (Chrome)                                   |
| Water Pressure            | Min 250kPa - Max 700kPa                                                        |
| Water Connection          | 1/2" BSP (G1/2)                                                                |
| Water Supply Requirements | Cold                                                                           |
| Water Valves              | Integrated 500kPa Pressure limiting valve and Dual Check Valve                 |
| Power Rating              | 0.18kW 220-240V 50Hz                                                           |
| Power Supply              | 1 x 10 Amp socket outlet                                                       |
| Dimensions                | W280mm x D406mm x H333mm                                                       |
| Product Approvals         | WaterMark, RCM, ARC                                                            |
| Warranty                  | 5 years (appliance warranty 36 months plus additional 24 months tank warranty) |

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

## BKL 2 HydroTap 05 v1 00 02 21 CS Home

## HydroTap G5 CS Home

shown with "Classic Plus" Tap

