



# B-5000

## Instant Boiling and Chilled Filtered Water System



Dual temp dispenser pictured on optional Font



Underbench boiling and chilled module



Standard dual temp dispenser

### Benefits

- Boiling and chilled water at the touch of a lever
- No cupboard ventilation required
- Concealed Safety Switch
- Unique Splash Free technology
- Lowest energy consumption
- Smallest Unit Footprint
- Works with Billi Font for flexible positioning
- Water within 1 degree of boiling
- Australian owned, designed and manufactured.



**Billi Pty Ltd**

42 Lucknow Crescent

Thomastown Victoria 3074 Australia

Telephone +613 9469 0400

Facsimile +613 9649 0400

Website [www.billi.com.au](http://www.billi.com.au)

As Billi Pty Ltd has a policy of continual improvement,  
all details are subject to change without notice.  
All goods sold are subject to our standard terms and conditions.

# B-5000

## Data Sheet

### Instant Boiling and Chilled Filtered Drinking Water

#### Specification and model selection guide

Product Number	Model Name	Initial Cup Delivery	Boiling Water Delivery (Cups per hour)	Chilled Water Delivery (Cups per hour)	height mm	width mm	depth mm
915000	B-5000	10	60	60	340	180	500

#### Water supply

A single 15mm (1/2") stop-tap with a male thread should be installed in an easily accessible position. The water supply must be microbiologically safe to drink, with a minimum dynamic water pressure of 250kPa.

#### Power supply

A standard 10 amp power outlet is required in the cupboard area where the unit is to be installed. All B-5000 models are supplied with a 1 metre flex cord and plug.

#### Warranty

All components of the B-5000 are covered by a 24-month\* warranty. Filter cartridges are a consumable and are not covered by warranty, as water conditions and usage vary.

\* 24-month warranty dependant on installation by Billi service technician.

#### Disability Conscious design

Designed for all users, the B-5000's lever operations meet current Australian Standards relating to access for people with a disability.

#### Technical Advice

Contact Billi Pty Ltd on 1300 300 316

1 cup = 170ml. Based on the initial number of cups of chilled water immediately available, drawn at one cup every 10 seconds. Consideration may be need for usage patterns and draw off methods.

#### Options and accessories

— Finishes: Standard finish for the B-5000 dispenser is bright chrome. Optional Finishes—Brushed chrome or black chrome.

— Billi Font: Allows the B-5000 to be located away from sink areas and is finished in polished stainless steel.

— Dispenser Riser: 65mm dispenser extension. Supplied standard with the Billi Font.

— Tubing extension kit: Allows the dispenser to be offset from the under-bench unit.

#### Leakguard detection system

With the B-5000, there is no need to worry about water leakages. To ensure peace of mind, a watertight base tray and water detection system have been incorporated into the system's design. If a water leakage should occur, the water supply is instantly shut off.

#### Easy installation

The B-5000 Dispenser features a unique top-mounting system, making it simple to install. There is no need to reach up behind sink bowls to secure clamps or tubes—the 'snap-fit' base is secured into the mounting hole, pipe work is fed through from the top and the dispenser securely clips into place.

#### Certifications

Every Billi drinking water appliance is manufactured under a certified quality control system. The B-5000 has been tested and complies with all required standards, including: Watermark Licence Number 21882; tested to ATS 5200.105:2005; AS/NZS ISO 9001 Certificate Number QEC 11627; C-Tick approved; complies with AS1428 requirements for access for the disabled. Electrical Compliance Number CS100600V.

