

R134A:

Technical data	V30SG	V50SG	V30SG"e'	V40SG"e"	V50SG"e"	V30SG"2e"	V40SG"2e"	V50SG"2e"	V50DG"2e"
Models									
Capacity750ml	35	50	35	40	50	Upper 10	Upper 16	Upper 14	Left 21
						Lower 20	Lower 22	Lower 34	Right 21
Net capacity	123L	161L	122L	150L	161L	114L	140L	151L	145L
Pre-set temp in degrees	Normal	Normal	12	12	12	upper 6	upper 6	upper 6	Right 7
	(10-14)	(10-14)				Lower 12	Lower 12	Lower 12	Left 12
Adjustable temp in degrees	5 to 18	5 to 18	5 to 18	5 to 18	5 to 18	upper 5-10	Upper 5-10	Upper 5-10	Right 5-18
						Lower 10-18	Lower 10-18	Lower 10-18	Left 5-18
Power Input	140W	140W	120W	140W	140W	120W	140W	140W	120W
Heater	--	--	--	--	--	Yes	Yes	Yes	Yes
Freestanding or Built-in	Freestanding	Built-in	Freestanding	Built-in	Built-in	Freestanding	Built-in	Built-in	Built-in
No.of wooden shelf: (*)	4 (max 6)	4 (max 7)	4 (max 6)	5	4 (max 7)	4 (max 5)	4(max5)	4 (max 6)	14
Ambient temp in degrees	18-35	18-35	18-35	18-35	18-35	0-35	0-35	0-35	18-35
Climate Class	T	T	T	T	T	T	T	T	T
Net dim in mm WDXH	493x588x840	605x605x875	493x588x840	595x572x820	605x605X875	493x588x840	595x572x820	605x605X875	605*602*875
Gross dim in mm WDXH*	550x650x880	680x725x935	550x650x880	655x665x875	680x725x935	550x650x880	655x665x875	680x725x935	675*685*910
Net weight	38 kgs	52 kgs	38 kgs	44 kgs	52 kgs	43 kgs	50 kgs	55 kgs	59 kgs
Gross weight	42 kgs	56 kgs	42 kgs	48 kgs	56 kgs	47 kgs	54 kgs	59 kgs	63 kgs

R600a:

Technical data	AL- V30SG"e'	AL- V40SG"e"	AL- V30SG"2e"	Al- V40SG"2e"	AL- V40DG"2e"
Models					
Capacity750ml	35	40	Upper 10	Upper 16	Left 19
			Lower 20	Lower 22	Right 19
Net capacity	123L	150L	114L	140L	135L
Pre-set temp in degrees	12	12	upper 6	upper 6	Right 7
			Lower 12	Lower 12	Left 12
Adjustable temp in degrees	5 to 18	5 to 18	upper 5-10	Upper 5-10	Right 5-18
			Lower 10-18	Lower 10-18	Left 5-18
Power Input	87W	100W	87W	100W	107W
Heater	--	--	Yes	Yes	Yes
Freestanding or Built-in	Freestanding	Built-in	Freestanding	Built-in	Built-in
No.of wooden shelf: (*)	4 (max 6)	5	4 (max 5)	4(max5)	12
Ambient temp in degrees	18-35	18-35	0-35	0-35	18-35
Climate Class	T	T	T	T	T
Net dim in mm WDXH	493x588x840	595x572x820	493x588x840	595x572x820	595*573*820
Gross dim in mm WDXH*	550x650x880	655x665x875	550x650x880	655x665x875	655x665x875
Net weight	38 kgs	44 kgs	43 kgs	50 kgs	50 kgs
Gross weight	42 kgs	48 kgs	47 kgs	54 kgs	54 kgs

(*) Subject to changes accordingly to various references and models modifications.

Standard features:
Compressor operated: R134a or R600a
- Available in rated voltage/frequency (as per country's requirements): 100V/50/60Hz, 220V/50/60Hz, 115V/50Hz
- Automatic defrost
- Humidity : 65% RH +/-10% RH
- Black outer and inner finish
- Internal light
- Adjustable feet x 4
- Double glass door with 3rd acrylic layer
- Glass door opening stainless steel or alloy finish on option ref “ss” or “al”
* Based on carton box packing dimensions/weight

