



# HYDROTAP G5 BA ARC BRUSHED CHROME

**BOILING****AMBIENT****FILTERED**

## Order Code H52785Z01AU

Zip HydroTap Design Range Boiling, Ambient, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.



|                    |             |
|--------------------|-------------|
| Manufacturing Code | H52785Z01AU |
|--------------------|-------------|

|          |             |
|----------|-------------|
| Capacity | Residential |
|----------|-------------|

|                    |             |
|--------------------|-------------|
| Disability Options | Unavailable |
|--------------------|-------------|

|     |                                                    |
|-----|----------------------------------------------------|
| Tap | Zip HydroTap Design Range ARC Tap (Brushed Chrome) |
|-----|----------------------------------------------------|

|                |                         |
|----------------|-------------------------|
| Water Pressure | Min 170kPa - Max 700kPa |
|----------------|-------------------------|

|                  |                 |
|------------------|-----------------|
| Water Connection | 1/2" BSP (G1/2) |
|------------------|-----------------|

|                           |      |
|---------------------------|------|
| Water Supply Requirements | Cold |
|---------------------------|------|

|              |                                                                |
|--------------|----------------------------------------------------------------|
| Water Valves | Integrated 500kPa Pressure limiting valve and Dual Check Valve |
|--------------|----------------------------------------------------------------|

|              |                      |
|--------------|----------------------|
| Power Rating | 1.35kW 220-240V 50Hz |
|--------------|----------------------|

|              |                          |
|--------------|--------------------------|
| Power Supply | 1 x 10 Amp socket outlet |
|--------------|--------------------------|

|            |                          |
|------------|--------------------------|
| Dimensions | W280mm x D313mm x H333mm |
|------------|--------------------------|

|                   |                |
|-------------------|----------------|
| Product Approvals | WaterMark, RCM |
|-------------------|----------------|

|          |                                                                                |
|----------|--------------------------------------------------------------------------------|
| Warranty | 5 years (appliance warranty 36 months plus additional 24 months tank warranty) |
|----------|--------------------------------------------------------------------------------|

## Installation Requirements

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com](http://www.zipwater.com)'

### Installation Detail

