Goldair



Operating Instructions

3.5kW Portable Air Conditioner



Model: GCPAC12

General Care and Safety Guide

Thank you for choosing this Goldair product. This Goldair appliance has been designed and manufactured to high standards of engineering and with proper use and care, as described in this leaflet, will give you years of useful service. Please read these instructions carefully and keep them for future reference.

- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
- 2. Children should be supervised to ensure that they do not play with the appliance.
- 3. If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.
- 4. Ensure that the fan is switched off from the supply mains before removing the guard.
- 5. Use only the voltage specified on the rating plate of the appliance.
- 6. Keep all objects at least 1 Metre from the front, sides and rear of the appliance
- 7. This appliance is intended for household use only and not for commercial or industrial use.
- 8. Use this appliance only as described in this manual. Any other use is not recommended by the manufacturer and may cause fire, electric shock or injury.
- The common cause of overheating is deposits of dust or fluff in the appliance. Ensure these deposits are removed regularly by unplugging the appliance and vacuum cleaning the air vents and grills.
- 10. Always unplug appliance when not in use.
- 11. When the appliance has been unpacked, check it for transport damage and ensure all parts have been delivered. If parts are missing or the appliance has been damaged, contact the Goldair Customer Services Team.
- 12. If your appliance does not work, or is not working properly, contact the place of purchase. Repair work on the appliance by unqualified persons can cause serious risk to the user.
- 13. Ensure hands are dry before handling the plug or the main unit.
- 14. Carry out regular checks of the supply cord to ensure no damage is evident.
- 15. Ensure that the cord is fully extended (not coiled) while in use.
- 16. Avoid contact with the moving parts. Keep hands, hair, clothing, away from blade of the fan during operation to reduce the risk of injury to person and/or damage to the unit.
- 17. Switch off and use handles provided when moving.
- 18. It is recommended that this fan is plugged directly into the wall socket.
- A correctly specified, undamaged extension cord may be used with this fan provided it is used in a safe manner.
- 20. Never place appliance close to radiant heat source.
- 21. Never operate in areas where petrol, paint or other flammable liquids are used or stored.
- 22. Never use the appliance to dry clothes.
- 23. Never insert or allow foreign objects to enter any ventilation or exhaust opening, as this may cause an electric shock, fire or damage to the appliance.
- 24. Never use abrasive cleaning products on this appliance. Clean with a damp cloth (not wet) rinsed in hot soapy water only. Always remove plug from the mains supply before cleaning.
- 25. Never connect the appliance to mains supply until completely assembled and adjusted.
- 26. Never remove plug from power socket until the appliance has been switched off.
- 27. Never remove plug from power socket by pulling cord always grip plug.

General Care and Safety Guide

- 28. Never twist, kink or wrap the cord around the appliance, as this may cause the insulation to weaken and split. Always ensure that all cord has been removed from any cord storage area and is unrolled before use.
- 29. Never use this appliance in the immediate surrounds of a bath, a shower, or a swimming pool or other liquids. The appliance must not be immersed in any liquids.
- 30. Due to the risk of injury, never use this appliance for any purpose other than its intended use. This appliance is intended for use in household and similar applications such as staff kitchen areas in shops, offices and other working environments; farm houses, by clients in hotels, motels, bed and breakfast type environments and other residential type environments
- 31. Never use this appliance outdoors.
- 32. Never operate the appliance with a damaged cord or plug, after it malfunctions, or if it has been damaged in any manner. Have the appliance checked and repaired by a qualified electrician if repair is necessary.
- 33. Never place the unit in wardrobes or other enclosed spaces as this may cause fire hazards.

General Care and Safety Guide

Goldair



PORTABLE AIR CONDITIONER

MODEL: GCPAC12

SUPPLY: 220-240VAC 50Hz

RATED INPUT COOLING: 1357W

COOLING CAPACITY: 12000Btu/h (3.53kW)

REFRIGERANT: R290 / 230g
PERMISSIBLE EXCESSIVE Discharge 1.8MPa
OPERATING PRESSURE: Suction 0.6Mpa

MAX ALLOWABLE PRESSURE: 3.0MPa
AIR FLOW: 400m³/h
SOUND POWER LEVEL: 62dB(A)

IPX0

APPROVAL NO: EESS-200287-0

QC PASSED: MADE IN CHINA



DO NOT COVER



Appliance is filled with flammable gas R290.



Before using the appliance, read the manual.



Before installing the appliance, read the installation manual.



Any repairs required, contact the nearest authorised Service Centre and strictly follow the manufacturer's instruction only.



Caution, risk of fire

WARNING: Appliance shall be installed, operated and stored in a room with a floor area larger than 11m².


Do not use any means to accelerate the defrosting process or to clean ,other than those recommended by the manufacturer.

The appliance shall be stored in a room without continuously operating ignition sources. (example: open flames, an operating gas appliance or an operating electric heater).

Do not pierce or burn.

Be aware that refrigerants do not have any odour.

Components



Installation


NOTE: The air-conditioner should be installed on a flat surface with at least 300mm clearance all around, including from the top of the unit as it is important that the air outlet is not blocked. Power supply must be nearby.

WARNING: THIS APPLIANCE MUST BE INSTALLED, OPERATED AND STORED IN A ROOM WITH A FLOOR AREA LARGER THAN 11m²

Do not install and use the appliance in the bathroom or other humid environments.

Install the heat pipe assembly (as shown in Figure 1).

Screw the heat pipe assembly (exhaust fitting end) into the exhaust port on the rear panel (counterclockwise).



Install the window sealing plate assembly


Half open the window, and mount the window sealing plate assembly to the window (as shown in Figure 2 and Figure 3); the assembly can be placed in horizontal and vertical direction. Pull various components of the window sealing plate assembly open, adjust their opening distance to bring both ends of the assembly into contact with the window frame, and fix various components of the assembly.

You may require a glazier to cut a hole in your window pane to fit the exhaust hose fixing clip.

Important Notice


The length of the exhaust hose shall be 280~1,500mm, and this length is based on the specifications of the air conditioner. Do not use extension tubes or replace it with other different hoses, or this may cause a malfunction. Exhaust must be unobstructed; otherwise it may cause overheating.





Control Panel and Remote Control

This Portable Air Conditioner is designed to be operated in cooling mode, heating mode or dehumidifying mode. When switching between these functions keep an interval of at least 3 minutes between each ON/OFF.



Allow the refrigerant to settle by leaving the appliance to stand for two hours after transport or after the unit has been on its side.

Ensure the unit is in the OFF setting before connecting it to the mains supply.

When the appliance is powered on for the first time, it will beep, and then the unit will be in standby.

Power Button

Press the button to turn the unit ON and OFF.

Mode Button

Press the button to switch between Cooling \rightarrow Dehumidification \rightarrow Fan modes.

Fan Speed Button

In cooling, fan or heating mode press the button to select between high, medium or low fan speed operation. In dehumidification mode the fan will automatically be set to low speed operation. This cannot be changed.

Temperature Setting

To set the desired temperature, press UP or DOWN button. The range is 16-31°C.

This function is not available in fan or dehumidification mode.

Simultaneously press both buttons to switch between Celsius (°C) and Fahrenheit (°F).

Timer Setting

The timer can be set to turn the unit ON or OFF from 1-24 hours.

To set the timer to turn the unit OFF, press the TIMER button while the unit is operating and set the desired number of hours before the unit turns off.

To set the timer to turn the unit ON, press the TIMER button while the unit is in standby and set the desired number of hours before the unit turns on.

Sleep Mode

In the Cooling Mode, Press the UP and Fan buttons together to turn on sleep mode. The unit will work in Energy-Saving and quiet mode. In Cooling sleep mode, the temperature will rise 1°C after one hour and rise 1°C after another one hour, and then stay the same.

Note: You cannot not use sleep mode in the Dehumidifying or Fan modes.

Operating your Air Conditioner

REMOTE CONTROL

The remote control has the same functions as the unit control panel.



Power Button

Press the button to turn the unit ON and OFF.



Mode Button

Press the button to switch between Cooling \rightarrow Dehumidification \rightarrow Fan modes.



Fan Speed Button

In cooling or fan mode press the button to select between high, medium or low fan speed operation.

In dehumidification mode the fan will automatically be set to low speed operation. This cannot be changed.



Temperature Setting

To set the desired temperature, press UP or DOWN button. The range is 16-31°C.

This function is not available in fan or dehumidification mode.

Simultaneously press both buttons to switch between Celsius (°C) and Fahrenheit (°F).



Timer Setting

The timer can be set to turn the unit ON or OFF from 1-24 hours.

To set the timer to turn the unit OFF, press the TIMER button while the unit is operating and set the desired number of hours before the unit turns off.

To set the timer to turn the unit ON, press the TIMER button while the unit is in standby and set the desired number of hours before the unit turns on.



Sleep Mode

In the Cooling Mode, Press the SLEEP button to turn on the sleep mode. The unit will work in Energy-Saving and quiet mode.


Note: You cannot not use sleep mode in the Dehumidifying or Fan modes.



Press to switch between Celsius (°C) and Fahrenheit (°F).



Press to activate the swinging louvre.



Care and Maintenance

Self Evaporating System

As part of the air conditioning process, water is extracted and builds up on the evaporator surface. The water will drop down from evaporator to the bottom of the unit. There is spray motor at the bottom which sprays the water to the surface of condenser. As the condenser surface temperature is very high, when the water touches the condenser surface, it will evaporate from water to air and be expelled out through the exhaust hose.

Water Full Indicator

If for some reason not all the water evaporates, some my stay in the bottom of the unit. It only holds about 1L and this can be emptied through the drain at the bottom of the unit.

Manual Drainage

The unit will stop once it has filled with water. Turn off the unit and unplug the power plug.

Move the unit carefully, so as not to spill the water in the water pan at the bottom of the body.

Find a place to drain the water or place a bucket below the water outlet on the back of the unit.

Unscrew the drainage cover and unplug the water plug, the water will automatically flow into the water container.

During drainage, the body can be tilted slightly backwards.

When the water is discharged, replace the water plug, and retighten the drainage cover.

Allow unit to sit for at least 5 minutes before turning back on.


Continuous Drainage

The unit can be operated with permanent drainage but you need to be able to allow the water to drain outside via gravity.

When the appliance is in Dehumidify mode, the continuous drainage hose needs to be inserted into the top drain hole. Remove the water plug to allow the hose to be inserted.

When the appliance is in Cooling or Heating mode, the continuous drainage hose needs to be inserted into the water tank drain hole at the bottom. Remove the water plug to allow the hose to be inserted.





Do not use this Air Conditioner with a programmer, remote-control system, separate timer or any other device that switches the Air Conditioner on automatically.

Care and Maintenance


CARE AND CLEANING

Clean the upper filter screen frame

- Clasp the wedging block of the EVA filter screen frame with hands. Force down from the
 outside to remove the EVA filter screen frame. Unscrew four screws fixing the EVA filter
 screen and the rear housing to remove the EVA filter screen (as shown in the below figure)
- Put the EVA filter screen into warm water with neutral detergent (about 40 °C / 104 °F) and dry it in the shade after rinsing clean.

Clean the lower filter screen frame

- Hold the handle of the CON filter screen frame, and pull it outward gently to remove it.
- Put the CON filter screen into warm water with neutral detergent (about 40 °C) and dry it in the shade after rinsing clean.



NEVER USE UNIT WITHOUT THE AIR FILTER.

The exterior may be cleaned with a soft, dry cloth. If the device is extremely dirty wipe the device with a slightly damp (not wet) cloth. Never spray the device with water. DO NOT immerse the unit in water and never allow water to enter the motor housing. DO NOT use harsh chemicals to clean the unit.

Do not attempt to dismantle the Air Conditioner. There are no user serviceable parts. For service or repair, contact an authorised electrical service technician.

STORAGE

To store the unit, remove the plug from the socket. Remove the rubber plug from the drainage hole at the bottom of unit, and connect a drain hose to the lower fixing clip. All the water in the water tank will drain out. Allow the Container and the Air Conditioner to dry completely. Clean the air filter. Refit the rubber plug. Store the device in a dust-free location, preferably covered with a sheet of plastic.

WiFi – Downloading and Setting up APP

This APP is supported only on 2.4GHz Wi-Fi channels. Please ensure your phone is 2.4GHz capable

Note this device will only work within your home WIFI system. This does not operate on 3G or 4G internet connections. You will need a connection to your home Wi-Fi.

Download Goldair mobile APP

- Open the APP Store or Google Play on your mobile phone.
- Open 'Search' and enter 'Goldair'
- Click 'GET' and begin to download and install.

Once downloaded to your phone open the APP

- Tap REGISTER near the bottom of the screen.
- Read and agree to the Privacy Policy.
- Add your email address.
- Tap 'Obtain verification code'


You will then receive an email with a verification code.

- Enter the verification code from your email.
- Create a password.
- Then tap confirm.

If you haven't received a verification code via email, tap the resend button and when the verification code is received follow above steps.

Your APP is now registered and ready for pairing to your device.







Pairing APP to Device

Details for pairing this heater to the Goldair App can be found at the below website link.

Either scan the QR code below or enter the website into your browser.

New Zealand Products

https://www.goldair.co.nz/ goldair-app

Australia Products

https://www.goldair.com.au/ goldair-app

Pairing Mode

To connect to the Goldair app you must ensure that your device is in pairing mode which is where the Wifi Icon is flashing.

Most products will be in pairing mode after switching the device on but if it is not:

- Put device on STAND-BY mode (ON at the wall but device is OFF)
- Hold down "FAN SPEED" button for around 5 seconds or until the Wifi icon begins to flash.

Troubleshooting

Problems	Reasons	Solutions	
	There is no electricity.	Turn it on after connecting it to a socket with electricity. Discharge the water inside. Recommend to use the machine in at the temperature of 7-35 °C (44-95 °F).	
	The water-full indicator will flash.		
	The ambient temperature is too low or too high		
The air conditioner does not work.	In cooling mode, the room temperature is lower than the set temperature; in heating mode, the room temperature is higher than the set temperature.		
	In dehumidification mode, the ambient temperature is low.	The machine is placed in a room with an ambient temperature of greater than 17 $^{\circ}$ C (62 $^{\circ}$ F).	
	There is direct sunlight.	Pull the Curtain.	
The cooling or heating effect is not good	Doors or windows are open; there are a lot of people; or in cooling mode, there are other sources of heat.	Close doors and windows.	
	The filter screen is dirty.	Clean or replace the filter screen.	
	The air inlet or outlet is blocked.	Clear obstructions.	
Loud Noise	The air conditioner is not placed on a flat surface.	Put the air conditioner on a flat and hard place (to reduce noise). Wait for 3 minutes until the	
	Frost production starts.		
Compressor does not work.	Overheat protection starts.	temperature is lowered, and then restart the machine.	
The remote control does	The distance between the machine and the remote control is too far.	Move the remote control closer to the air conditioner, and make sure that the remote control directly faces to the direction of the remote control receiver.	
not work.	The remote control is not aligned with the direction of the remote control receiver.		
	Batteries are dead.	Replace batteries.	
Displays 'E1'.	The room temperature sensor is abnormal.	Check the room temperature sensor and related circuitry.	
Displays 'E2'	The pipe temperature sensor is abnormal.	Check the pipe temperature sensor and related circuitry.	

PROOF OF PURCHASE

To receive warranty retain receipt as proof of purchase. (Refer to back of booklet).



SUPPORT AND TECHNICAL ADVICE

Goldair – New Zealand Monday – Friday 8am-5pm Phone +64 (0)9 917 4000 Phone 0800 232 633 info@cdb.co.nz Goldair – Australia Monday – Friday 8am-5pm Phone +61 (0)3 9336 4423 Phone 1300 465 324 info@cdbgoldair.com.au



One Year Warranty

Thank you for purchasing this Goldair product. Your product is warranted against faults and manufacture when used in normal domestic use for a period of **one year**. In non-domestic use Goldair limits the voluntary warranty to **three months**.

Goldair undertake to repair or replace this product at no charge if found to be defective due to a manufacturing fault during the warranty period.

This warranty excludes damage caused by misuse, neglect, shipping accident, incorrect installation, or work carried out by anyone other than a qualified electrical service technician.

PLEASE KEEP YOUR RECEIPT AS THIS WILL HELP VERIFY YOUR WARRANTY.

The benefits to you given by this warranty are in addition to other rights and remedies available to you under a law in relation to the goods or services to which this warranty relates.

In Australia, our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

In New Zealand this warranty is additional to the conditions and guarantees of the Consumers Guarantee Act (1993).

Goldair – New Zealand CDB Goldair PO Box 100-707 N.S.M.C Auckland

Phone +64 (0)9 917 4000 Phone 0800 232 633 www.goldair.co.nz Goldair – Australia CDB Goldair Australia Pty PO Box 574 South Morang Victoria, 3752

Phone +61 (0)3 9365 5100 Phone 1300 GOLDAIR (1300 465 324) www.goldair.com.au

Goldair One Year Warranty (IMPORTANT: Please complete and retain this warranty card)				
Name				
Address				
Place Of Purchase	Date of Purchase			
Name Of Product	Model Number			
Attach a copy of the purchase receipt to this warranty card				

Goldair





New Zealand PO Box 100707, North Shore Mail Centre, Auckland, 0745 www.goldair.co.nz

Australia PO Box 574, South Morang, Victoria, 3752 www.goldair.com.au