XS5990TST 60CM X-PRO SERIES REFRIGERATOR & TRI-MODE, **250L CAPACITY & 78L CAPACITY**













TRIMODE DRAWER









TOUCH CONTROL

SOFT CLOSE DRAWERS







SHOPPING MODE

PROVENT

OPTI-VIEW LED LIGHTS

ANTIBACTERIAL STAINLESS STEEL INTERIOR









AVAILABLE WITH LEFT OR RIGHT

24 MONTH WARRANTY









AN EXPRESSION OF QUALITY AND THE PINNACLE OF FOOD PRESERVATION

For those who prefer a more robust aesthetic design and commercial feeling, Fhiaba has developed the X-Pro series of wine preservation models realising exceptional solutions to the Wine Cellar within the interior of the kitchen space, without the compromise of comfort, functionality and design excellence.

Fhiaba is the only company in the world today with technology capable of managing three independent climate zones, for unrivalled, high-quality food storage. Fhiaba systems also feature lateral refrigeration, thereby allowing for maximum use of the full depth of the inner compartments

Exclusive Fhiaba technology makes it possible to combine the four "key variables" of refrigeration, to create and maintain perfectly balanced climates.

Accurate temperatures

Thanks to the numerous built-in sensors, the indicated temperature is always accurate.

Uniform ProVent Ventilation

The ProVent system uniformly distributes cold air to all parts of the fridge.

TriPro Refrigeration

The triple cooling system ensures each ingredient and dish gets the right micro-climate.

Humidity control

Our wine cellars offer three different humidity level settings: low, medium and high.





XS5990TST

60CM X-PRO SERIES REFRIGERATOR & TRI-MODE.

250L CAPACITY & 78L CAPACITY PRODUCT DETAIL

FEATURES

- Meticulously designed & built to withstand prolonged use
- X-Pro gives a commercial aesthetic to your kitchen
- Total No Frost 100% automatic system which eliminates the need to defrost the fridge, fresh food and freezer compartments. In addition it enables the temperature to be restored quickly after opening thanks to 'speed freezing'.
- Smart-touch TFT controls manages and monitors the entire fridge operation process is simple to use. Fridge, fresh food compartment and drawer temperatures are shown on the digital display
- Accurate temperatures. Thanks to the built-in thermostat, the temperature is always accurate
- Insulated variable speed compressor maintains precision temperature control with minimal vibration
- ProVent ventilation system encourages uniform distribution of cold air in all fridge compartments by laterally circulating air
- Uniform temperature throughout allowing for better food preservation conditions
- Independent ventilation for each storage compartment, resulting in uniform and precise temperature control, and ensuring optimum food preservation.
- Deep capacity within a standard depth is achieved by a side-mounted evaporator, giving greater interior space
- EvenLift[™] means shelves can slide up and down to be adjusted to any height in the fridge compartment
- Air purification system
- Two state of the art compressors and three evaporators ensure continuous operation, energy savings and quiet operation (41db)
- Antimicrobial EverCrisp[™] drawers prevent growth of micro-organisms and cross-contamination with beadblasted stainless steel
- Three independent electronically controlled cooling zones for maximum flexibility
- The patented Trimode drawer can operate in 3 different micro climates: freezer, Fresco and refrigerator.

INTERIOR

- Complete anti-bacterial stainless steel interior including shelves and side panels
- Soft-close doors and drawers in all compartments
 9 LED lights specifically positioned within the refrigerator ensure even light throughout, regardless of what is in the compartment & 2 LED light points illuminate the TRI-mode compartment
- Three adjustable glass Rack-and-Pinion Scrolling tempered glass shelves and one stationary base shelf.
- Shelves have aluminium profiles

- Two crisper drawers for multi-use preservation solutions.
 Low temperature with antibacterial stainless steel interiors & rounded corners promoting hygiene and easy cleaning
- Three adjustable door shelves
- Full extraction drawers with soft closing runners

TEMPERATURE

- One independent climatic zone +2 / + 8°C & low temp zone in the internal drawers
- TRI-mode adjustable temperature from -22°C + 8°C

DOOR

- Dual-movement patented hinge, with self-balancing movement ensures stability and resistance
- Pivoting door hinge system to be built-in
- Door open alarm
- Door opening angle: 105°

NOISE

Noise level - 41db

CAPACITY

- Refrigerator Use-able Storage Capacity:250L
- Tri-mode compartment (fridge / fresco / freezer): 78L

TECHNICAL

- Uniform 2120mm height across all X-Pro models
- Energy consumption: 322kw/yr
- Net Weight: 195kg
- Power lead length: 2m
- Front and rear adjustable feet up to 25mm height

ACCESSORIES

- KCCMT Joining kit separate upper grill models with stainless steel sides (Joining brackets, airflow separation included+anti-condensation kit)
- XPR0120TOP - XS599 + XS599 Single Grill Kit
- XPR0135TOP - XS749 + XS599 Single Grill Kit
- XPR0150T0P XS899 + XS599 Single Grill Kit
- KCCITX Joining kit with single upper grill models with stainless steel sides (Joining brackets, airflow separation included+anti-condensation kit)
- KITNRG899749 Transformer for network integration with alternative energy

fhiaba.com.au

FOLLOW US ON:

P: 1300 694 583

Eurolinx Showrooms are open Tuesday - Friday 9am - 5pm, Saturday - 10am - 4pm, Sunday and Monday - closed* *Perth: Tuesday - Friday 10am - 4pm, Saturday, Sunday and Monday - closed



/fhiaba_refrigerationau/

NEW SOUTH WALES (Head Office)

48-50 Moore Street Leichhardt VICTORIA

1211 Toorak Road Camberwell **QUEENSLAND** 1/42 Cavendish Road Coorparoo **WESTERN AUSTRALIA**Unit 10/55 Howe Street
Osborne Park

2/4 Page 01052020

DISCLAIMER


Eurolinx PTY LTD, is continually seeking ways to improve the design specifications, aesthetics and production techniques of its products. As a result alterations to our products and designs take place continually. Whilst every effort is made to produce information and literature that is up to date, this brochure should not be regarded as an infallible guide to the current specifications, nor does it constitute an offer for the sale of any particular product. Product dimensions indicated in our literature is indicative only. Actual product only should be used to define dimension cut outs. Distributors, and retailers are not agents of Fhiaba and are not authorised to bind Fhiaba by any express or implied undertaking or representation.








PRODUCT SPECIFICATIONS AND DIMENSIONS
















For installation specifications, please consult with Fhiaba. For optimum installation, we recommend using the actual product as the best guide.

FOLLOW US ON:



/fhiaba_refrigerationau/

fhiaba.com.au

Eurolinx Showrooms are open Tuesday - Friday 9am - 5pm, Saturday - 10am - 4pm, Sunday and Monday - closed* *Perth: Tuesday - Friday 10am - 4pm, Saturday, Sunday and Monday - closed

NEW SOUTH WALES (Head Office)

48-50 Moore Street Leichhardt

VICTORIA

1211 Toorak Road Camberwell

QUEENSLAND

1/42 Cavendish Road Coorparoo

WESTERN AUSTRALIA

Unit 10/55 Howe Street Osborne Park

DISCLAIMER


Eurolinx PTY LTD, is continually seeking ways to improve the design specifications, aesthetics and production techniques of its products. As a result alterations to our products and designs take place continually. Whilst every effort is made to produce information and literature that is up to date, this brochure should not be regarded as an infallible guide to the current specifications, nor does it constitute an offer for the sale of any particular product. Product dimensions indicated in our literature is indicative only. Actual product only should be used to define dimension cut outs. Distributors, and retailers are not agents of Fhiaba and are not authorised to bind Fhiaba by any express or implied undertaking or representation.

XS5990TST 60CM X-PRO SERIES REFRIGERATOR & TRI-MODE, **250L CAPACITY & 78L CAPACITY**

INSTALLATION INFORMATION








The Lateral Connection Kit (KCLIT/KCLIH/KCLMT/ KCLMH) is supplied on all models (except in the unit with stainless steel sides) and consists of a connection element (A) and a aluminium frame (B).


Prominent installation






The Lateral Connection Kit (KCLIT/KCLIH/KCLMT/ KCLMH) is supplied on all models (except in the unit with stainless steel sides) and consists of a connection element (A) and a aluminium

Electrical and Water connection



Electrical and Water connection behind the unit



For installation specifications, please consult with Fhiaba. For optimum installation, we recommend using the actual product as the best guide.

FOLLOW US ON:



/fhiaba_refrigerationau/

fhiaba.com.au

Eurolinx Showrooms are open Tuesday - Friday 9am - 5pm, Saturday - 10am - 4pm, Sunday and Monday - closed* *Perth: Tuesday - Friday 10am - 4pm, Saturday, Sunday and Monday - closed

NEW SOUTH WALES (Head Office)

48-50 Moore Street Leichhardt

VICTORIA

1211 Toorak Road Camberwell

QUEENSLAND

1/42 Cavendish Road Coorparoo

WESTERN AUSTRALIA

Unit 10/55 Howe Street Osborne Park

DISCLAIMER

Eurolinx PTY LTD, is continually seeking ways to improve the design specifications, aesthetics and production techniques of its products. As a result alterations to our products and designs take place continually. Whilst every effort is made to produce information and literature that is up to date, this brochure should not be regarded as an infallible guide to the current specifications, nor does it constitute an offer for the sale of any particular product. Product dimensions indicated in our literature is indicative only. Actual product only should be used to define dimension cut outs. Distributors, and retailers are not agents of Fhiaba and are not authorised to bind Fhiaba by any express or implied undertaking or representation.