


iQ300 EH651FDC1E 60 cm Induction cooktop





Induction cooktop with innovative features that enable highly flexible cooking in any situation.

✓ fryingSensor: maintains the desired pan temperature automatically
after heating up to avoid scorching.

Feature

Technical Data

Product name/family : Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time: 3

Type of control setting devices : TouchSlider (Timer)

Required niche size for installation (HxWxD): 51 x 560-560 x 490-500

Width of the product (mm): 592

Dimensions of the product (mm): 51 x 592 x 522

Net weight (kg): 13.0 Gross weight (kg): 15.0 Residual heat indicator: Separate Location of control panel: Hob front

Basic surface material : Ceramic Color of surface : Black

Approval certificates : AENOR, CE Length electrical supply cord (cm) : 110

EAN code: 4242003697580

Electrical connection rating (W): 7400

Voltage (V): 220-240 Frequency (Hz): 60; 50



Optional accessories

HZ390230	System pan diameter 21cm
HZ390220	System pan diameter 19cm
HZ390210	System pan Ø 15cm
HZ390090	Wok Set consisting of 3 Items
HZ390030	set of 3 pots for induction hob



iQ300 EH651FDC1E 60 cm Induction cooktop

Feature:

Cooktop Type and Special Features

- 3 induction cooking zones
- Ring zone triple
- Cooking zone with special 5.5kW powerBoost
- powerBoost function for all cooking zones
- fryingSensor Plus with 4 temperature settings

Design

- U-Facette design
- New design (of printing)

Comfort & Convenience

- touchSlider control
- LED display and timer with auto switch off for all cooking zones
- ReStart Quickly reinstates previous settings
- QuickStart Quick and automatic first pot detection

Size & Power

- 17 power levels for each cooking zone
- Cooking zone rear left:
- 260 mm, 210 mm, 320 mm
- 3.3 kW, 2.2 KW, 2.6 KW / 3.7 KW, , 5.5 KW with powerBoost
- Cooking zone rear right:
 - 145 mm
- 1.4 KW / 2.2 KW with powerBoost
- Cooking zone front right:
- 210 mm
- 2.2 KW / 3.7 KW with powerBoost
- 7.4 kW total connected load

Safety and Environment

- Automatic pan recognition
- Automatic safety switch-off childproof lock
- 2-stage (h/H) digital residual heat indicator
- Energy efficiency display

Dimensions (WxD)

- Installation measurements: 560 mmx490 mm
- Length wire connection: 110 cm
- Min. worktop thickness: 30 mm



iQ300 EH651FDC1E 60 cm Induction cooktop

Dimensioned drawings min. 50 490-500⁺²0 *min. 40 min. 50 min. 600 * Minimum distance from the hob cut-out to the wall ** Recessed depth *** With fitted oven underneath min. 30, possibly more; see space requirements for the oven measurements in ***min.20 measurements in mm min. 65 min. 45 Drawer 20 ① Ventilation gap must be present. Measurements in mm Built-in cooker/ built-in oven ① Ventilation gap must be present All measurements in mm