



HYDROTAP G5 CS ELITE BRUSHED GOLD



CHILLED SPARKLING

FILTERED

Order Code H54787Z07AU

Zip HydroTap Design Range Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code	H54787Z07AU
Capacity	Residential

Tap	Zip HydroTap Design Range ELITE Tap (Brushed Gold)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	0.18kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W280mm x D406mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

BKL 2 HydroTap 05 v1 00 02 21 CS Home

HydroTap G5 V1.00 02/21 CS Home

Ventilation requirements Contact your local service provider if ventilation is not suitable

HydroTap Tap options

Font options

Clearance envelope

Position the Tap and the Command Centre as close together as possible.

Air outlet louvre (if required)
Cut-out in door/wall, towards
the top of the cabinet

Air inlet cut-out (required)
Cut-out in cabinet floor

Classic Plus

Elite Plus

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for
HydroTap Tap

**Raised Font
with 135mm Extension**

**Font
with 135mm Extension**

Cutting detail

Cutting detail

**HydroTap G5
CS Home**

shown with "Classic Plus" Tap

SCALE 1:5
ALL DIMENSIONS IN MM (UNLESS OTHERWISE SPECIFIED). INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

