



WS461110
Warming drawer 400 series
Stainless steel-backed glass front
Width 60 cm, Height 14 cm

Handleless drawer
Bright interior light
Cushioned closing system
Hygienic stainless steel interior with glass bottom
4 power levels in the temperature range 40 °C to 80 °C (glass surface)
Also for preparing and cooking meals, and for keeping meals warm

Heating methods
Defrosting of meals/proving of yeast dough.
Preheating of small beverage containers.
Keeping meals warm/slow cooking meals.
Warming ovenware.

Handling
Rotary knob operation.
Recessed grip at the front bottom of the drawer.

Features
Net volume 19 litres.
Volume capacity: Dinner service for 6 people including ø 24 cm plates and soup bowls, additional bowls and a serving dish depending on size.
Heating under glass bottom for easy cleaning.
Fan for even heat distribution for fast warming ovenware.
Status display, visible in the glass front.
Glass bottom made of safety glass.
Usable interior dimensions
W 475 x H 86 x D 458 mm.
Max. load 25 kg.

Planning notes
The panel surface of the appliance extends 47 mm from the furniture cavity.
Installation of BS/BM/CM directly above WS in 59 cm niche without intermediate floor.
The socket can be planned behind the appliance.

Connection
Total connected load 0.81 kW.
Connection cable 1.5 m, detachable.

Characteristics
Built-in / Free-standing
Built-in
Color / Material Front
Stainless steel
Maximum number of plates
12
Maximum number of espresso cups
80
Dimensions of the product (mm)
140 x 590 x 535
Dimensions of the packed product (HxWxD) (mm)
210 x 650 x 730
Required niche size for installation (HxWxD)
140 x 560 x 550
EAN code
4242006172978

Consumption and connection features
Electrical connection rating (W)
810
Current (A)
10
Voltage (V)
220-240
Frequency (Hz)
50; 60
Plug type
Gardy plug w/ earthing

2019-09-24
Page 1

Color Variants
WS461110
Stainless steel-backed glass front
Width 60 cm, Height 14 cm

Side view of WS 461 below BS, BM, CM

