


V-ZUG Ltd

Industriestrasse 66, P.O.Box 59, 6301 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure DH-L8 / 11



Selected appliance

- Article no.: 6400160003
- Short designation: DHL8 EU 10
- Standard width: 80.0 cm
- recirculation air
- Front design: Stainless steel
- Installation method: integrated range hood
- Recirculation air filter: Standard charcoal filter

Also available with/as (*)

- Extracted air Yes

(*) Not all combinations are available. Ask your retailer for advice.

Details DHL8 EU 10

Design

- Standard width: 80.0 cm
- recirculation air
- Front design: Stainless steel
- Installation method: integrated range hood
- Recirculation air filter: Standard charcoal filter

Dimensions

- Appliance height: 300.0 mm
- Front height: 300.0 mm
- Height: Extracted air/recirculation air: 30.0 cm
- Appliance width: 800.0 mm
- Appliance depth: 300.0 mm
- Max. appliance depth: 300.0 mm
- Empty weight: 25.5 kg

Display and operation

- Controls: dial
- Fan power level display
- Lighting: LED
- Number of lights: 4
- Grease filter cleaning indicator

Energy

- Energy efficiency rating: C
- Annual energy consumption: 90.8 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 22.9
- Fluid dynamic efficiency rating: C
- Type of connection: 220-240 V~
- Nominal lighting output (quantity x W): 4 x 3 W
- Frequency (1): 50/60 Hz
- Connected loads: 0.2 kW
- Fuse protection: 10.0 A
- Plug type: Schuko 16A
- Plug type B: AS/NZS 3112
- Connection cable: 1.5 m

Range hood features

- Power levels: 4
- Remote control: No
- Fleece grease filter: 1
- Side exhaust
- Non-return flap, integrated/attached: included

Functions

- Intensive setting
- Automatic after-running time

Additional data

- Exhaust air connection (diameter): 150.0 mm
- Lighting efficiency: 32.0
- Illumination on cooking surface: 382.0 lux
- Grease absorption capacity rating: E
- Extracted air output, intensive setting: 563 m³/h
- Extracted air output, max. setting: 469 m³/h
- Extracted air output, min. setting: 228 m³/h
- Extracted air noise output, intensive setting: 61.0 dB(A)
- Extracted air noise level, max. setting: 57.0 dB(A)
- Extracted air noise output, min. setting: 40.0 dB(A)
- Recirculation air output, intensive setting: 322 m³/h
- Recirculation air output, max. setting: 233 m³/h
- Recirculation air output, min. setting: 146 m³/h
- Motor(s): 1
- Motor output: 188 W
- Feature level: 3

Service and interfaces

- Warranty: 2 years