

Serie | 6 Hoods**DHL785BAU**
70 cm Integrated Rangehood

The integrated rangehood: offers a sleek and seamless design in the kitchen with fully integrated installation.

- **Extraction rate:** at 730 m³/h, it quickly ensures optimal kitchen air quality.
- Halogen lighting provides optimal, energy-efficient illumination of the cooktop.
- **Intensive speed setting with reset:** automatically resets the hood to regular speed setting after 6 min.
- **Especially quiet:** just 63 dB (540 m³/h) - 150 mm ducted.

Technical Data

Typology :	Traditional
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	150
Required niche size for installation (HxWxD) :	418mm x 676mm x 264mm
Minimum distance above an electric hob :	500
Minimum distance above a gas hob :	650
Net weight (kg) :	10.0
Type of control :	Electronic
Number of speed settings :	3
Maximum output air extraction (m ³ /h) :	630
Boost position output recirculating (m ³ /h) :	310
Maximum output recirculating air (m ³ /h) :	300
Boost position air extraction (m ³ /h) :	730
Number of lights :	2
Noise level (dB) :	66
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable aluminium
EAN code :	4242002831183
Connection Rating (W) :	315
Current (A) :	3
Voltage (V) :	220-240
Frequency (Hz) :	50
Plug type :	AU plug
Installation typology :	Half-integrated

**Optional accessories**

DHZ5605 : Recirculating kit

Serie | 6 Hoods

DHL785BAU

70 cm Integrated Rangehood

The integrated rangehood: offers a sleek and seamless design in the kitchen with fully integrated installation.

Design & Innovation

- Fully integrated rangehood
- Stainless steel
- Rim ventilation
-

Power and Mode of Operation


- 3 power settings plus intensive setting
- 730 m³/h max. extraction rate
- Ducted and recirculated-air operation
- Powerful single motor with twin fan

Comfort & Convenience

- Intensive operation automatic revert - 6min
- 63 dB (540 m³/h) - 150 mm ducted
- Electronic controls with low-lift push buttons
- 2 x 20W halogen lights
- Dual filter system with outer aluminium frame and inner metal grease filter
- Dishwasher safe metal grease filters
- Accessories required for recirculation mode: Charcoal filter

Dimensions (HxWxD)

- Appliance (WxD): 700 mm x 282 mm
- Appliance - Ducted (HxWxD): 418min - 418max x 676 x 264 mm
- Appliance - Re-circulated (HxWxD): 418min - 418max x 676 x 264 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

Serie | 6 Hoods**DHL785BAU****70 cm Integrated Rangehood**

measurements in mm