

# Ideal Tap

IWT-D-PSS-AU

IWT-D-MSS-AU

IWT-D-GSS-AU

IWT-D-BSS-AU

IWT-D-YSS-AU

IWT-D-RSS-AU



Polished  
Stainless Steel

Matte  
Stainless Steel



PVD Gun Metal Gray™  
Stainless Steel

PVD Satin Black  
Stainless Steel



PVD Brushed Gold  
Stainless Steel  
*Limited Edition*

PVD Polished Rose Gold  
Stainless Steel  
*Limited Edition*

## Specifications

Single-lever control ceramic disk cartridge  
Forward rotating COMFORTFEEL™ lever handle  
279 mm CENTERSTATION™ spout projection  
279 mm Pot fill height from deck to spout outlet  
Hand spray extends up to 660 mm from spout  
Q-Dock™ docking system holds hand spray in place  
Ergonomic slide switch to select Ideal Flow®, Laminar or Spray Flow  
Automatic return to laminar flow  
Concealed easy clean spray face  
Spout rotates 360°  
Quiet, smooth gliding hose  
Counterweight  
Dual check valves  
610 mm stainless steel flexible hoses 9.5 mm compression  
Maximum counter thickness 51 mm  
Minimum install hole diameter 35 mm  
Optional base ring included  
Total height 540 mm  
1.8 GPM maximum flow rate  
WELS Rating: 5 Star / 5 litres per min

## Construction

Solid 316L machined stainless steel construction  
Available in Polished, Matte, PVD Gun Metal Gray™, PVD  
Satin Black, PVD Brushed Gold, PVD Polished Rose Gold  
Indoor & outdoor  
Limited Lifetime Warranty  
Made in Italy

## Codes/Standards



Watermark AS/NZS 3718

