

Series 2, Gas cooktop, 60 cm, Stainless steel PBH6B5K90A



HEZ298105 Simmer plate HEZ298107 Wok ring

HEZ298114 Small pot support

HEZ32WA00 Wireless food thermometer

HEZ9SE040 4 pieces Set HEZ9SE060 6 pieces Set

The gas cooktop with easier cleaning thanks to increased spacing between the side-mounted control dials.

- Dishwasher-suitable pan supports: make cleaning your hob even easier.
- Continuous cast-iron pan support: for high firmness and stability of cookware.
- Wok burner: quick boiling or precise simmering.
- Safety gas cut-off: ensures safety by instantly cutting off gas supply if the flame goes out.
- Sword knobs: firmer grip and easy control of your gas hob.

Product name/family:gas hob w integrated controls Built-in / Free-standing:
Width of the appliance:
Dimensions (HxWxD):
Dimensions of the packed product (HxWxD): 166 x 798 x 596 mm
Net weight:
Gross weight:
Residual heat indicator:separate
Location of control panel:Lateral
Basic surface material:Stainless steel
Color of surface: Stainless steel
Length electrical supply cord:
EAN code:
Gas connection rating:8500 W
Fuse protection:3 A
Voltage:
Frequency: 50; 60 Hz





Series 2, Gas cooktop, 60 cm, Stainless steel PBH6B5K90A

The gas cooktop with easier cleaning thanks to increased spacing between the side-mounted control dials.

Design

- Stainless steel surface
- Enamelled cast-iron trivets with rubber feet

Usage convenience

- Sword control knobs, right sided: access knobs on the side with strong grip for effortless turning.
- One-hand electronic ignition via controls: just push and turn the knob to ignite the flame.

Burners and power

- 4 Gas burners
- Left front: Wok burner up to 15 Mj/h (depending on gas type)
- Left rear: Standard burner up to 6.5 Mj/h (depending on gas type)
- Right rear: Standard burner up to 6.5 Mj/h (depending on gas type)
- Right front: Economy burner up to 3.8 Mj/h (depending on gas type) $\,$

Cleaning

- Wider spacing between control dials for easier cleaning.
- Dishwasher suitable pan supports for easy cleaning.

Safety

- Flame failure device fitted to each individual burner: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)


- Preset of natural gas (10mbar)
- Nozzle set for Liquid gas nozzles (28-30/37mbar) included.
- Dimensions of the product (HxWxD mm): 51.8 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 490)
- Min. worktop thickness: 20 mm
- Power cord 1 m cable with plug

Accessories

- 1 x Wok attachment ring included



Series 2, Gas cooktop, 60 cm, Stainless steel PBH6B5K90A



- A: Min. distance from the hob cut-out to the wall
- **B**: Position of gas connection in the cut-out
- C: With fitted oven underneath possibly more; see space requirements for the oven