

CHILL'D OUT REFRIGERATOR SPECIFICATION

1			GFKC1	GFKC2
	Picture			
	Brand		Chill'd Out	Chill'd Out
	Product description		Undercounter Cooler,single door	Undercounter Cooler,double hinged door
	Type of appliance (FS=free standing / BI= built-in)		BI	BI
	Placement (Indoor/Outdoor)		out door /IPX4	out door /IPX4
	Climate class (N=16-32C,ST=18-38C,T=18-43C)		N, ST	N, ST
	Freezer star rating		n/a	n/a
	Approvals (CE/ROHS/UL/NSF/CB)		CE, ROHS, MEPS	CE, ROHS, MEPS
2	Key features			
	Gross capacity	Liter		
	Total net capacity	Liter	118	190
	330ml bottle pack out (Ø70 x H120mm)	pcs	138	190
	500ml bottle pack out (Ø70 x H170mm)	pcs	78	110
	facing per shelf	pcs	6	10
	Defrosting (Manual-Automatic)		automatic	automatic
	refrigerant charge	R134a/g R600a/g	120 55	165 68
	Foaming agent		Cyclopentane	Cyclopentane
3	Technical data			
	Voltage / frequency	V/Hz	220v-240v/50Hz	220v-240v/50Hz
	Input power / main fuse minimum	W /A	182	213
	Length of cable / incl. plug	cm	150	150
	Temperature range (from>to)	°C	0-10	0-10
	Energy consumption (EN153) per 24 h	kwh/24h	1.30	1.80
	Cooling system: (K=Compressor / A=Absorbition)		K	K
	Maximum noise level	dB(A)	45	45
	evaporator type		roll band type	roll band type
	condenser type		wire tube type	wire tube type
	condenser fan		1 pc	1 pc
	compressor make/model	R134a R600a	Donper S43CZ Donper S65CY	Donper S53CZ Donper S75CY
	compressor power	W	95	142
4	Aesthetics			
	Door		Insulated double -glazed heated glass door with Low E GlassGlass	Insulated double -glazed heated glass door with Low E GlassGlass
	Colours:			
	Cabinet		Stainless steel with mullion heaters	Stainless steel with mullion heaters
	Top		Stainless steel	Stainless steel
	Door glass		clear	clear
	Door frame		Stainless steel	Stainless steel
5	Equipment & accessories			
	Product classification (Super eco / Eco / Standard)		Eco	Eco
	Inside walls (Stainless steel / Aluminium / Synthetic mat.)		Aluminium	Aluminium
	cabinet external material		Stainless steel	Stainless steel
	Wall thickness	mm	40	40
	Head light box		n/a	n/a
	Interior light		yes	yes
	light type (fluorescent/LED)		LED	LED
	light switch		yes	yes
	door		Hinged Door	Hinged Door
	glass		Transparent	Transparent
	lock/key		yes	yes
	handle		Zin cast Chrome	Zin Cast Chrome
	Inner Fan		1 pc	1 pc
	Shelves / Baskets number	n°	2	4
	shelf material		Chromed wire shelf	Chromed wire shelf
	shelf dimension (W/D)	mm	456/360	374/326
	Defrost drain		yes,auto-evaporating	yes,auto-evaporating
	Adjustable thermostat		electronic controller	electronic controller
	temperature display		yes, digital	yes, digital
	Adjustable feet/stabilizer (front / rear)	n°	4 feet	4 feet
	Mobility wheels (front / rear)	n°	n/a	n/a
	self closing door		yes	yes
	branding available		yes	yes
	canopy branding dimensions (H/W)	mm	n/a	n/a
	side panel branding dimensions (H/W)	mm	826/447	826/447
	top panel branding dimensions (W/D)	mm	551/492	861/492
	product display area (H/W)	mm	668/462	668/335
6	Product net dimensions			
	Unit dimensions (H / W / D)	mm	840/555/495	840/865/495
	Inner dimensions (H / W / D)	mm	695/471/371	690/781/371
	depth with open lid	mm	1150	1150
	Net weight	kg	44.2	59.5KG
7	Packing dimensions & loadability			
	Packing dimensions (H / W / D)	mm	890/650/564	890/945/564
	Gross weight	kg	46.1	63.5KG