

DBI653IBW

General description

Turbo Drying™ - Fan assisted moist air extraction

Style

Installation type: Built under work top

Size: XL, 82 cm

Number of baskets: 3

15 place settings

8 Steel™ Construction, SCS+ (Super Cleaning System+)

Top cutlery tray: Top Tray with Instant Lift™; Top Tray with Instant Lift™; Rack for knives (top); Rack for bowls (top); Telescopic rails for top tray; Handle (top)

Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support

Lower rack type: Premium - foldable pin rows

Construction & Performance

Exterior float

8 Steel™ construction

Hidden heater

SCS+ (Super Cleaning System+)

Number of spray arms: 3

Number of spray zones: 8

Use & Flexibility

Number of place settings: 15 place settings

Number of baskets: 3

Top cutlery tray: Top Tray with Instant Lift™; Top Tray with Instant Lift™; Rack for knives (top); Rack for bowls (top); Telescopic rails for top tray; Handle (top)

Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support

Easy sliding telescope rails with ball bearings for the upper basket

Lower rack type: Premium - foldable pin rows

Dense basket wiring in both upper and lower basket

Required inlet water pressure: 0,03-1 MPa

Interaction & Control

Display type: LCD display

Customizable programs: Program memory

Number of programs: 12

Status LED light

Programs, options and modes

12 Programs: Eco wash; Hygiene wash; Time program; Plastic wash; Heavy wash;

Rinse and hold; Sanitation wash; Upper half wash; Lower half wash; Crystal glass;

Quick Pro wash; Self-cleaning

Delayed start: Variable start delay up to 24 hours

Multi tablet function

Super rinse

Time set

Green mode

Speed mode

Night mode

Intensive mode

Extra dry

High temperature

Super rinse

Design & Integration


From front adjustable rear foot

Water connection: Size: 3/4" Can be connected to hot or cold water

Niche dimensions (HxWxD): 82 x 60 x 56 cm

Height setting: 50 mm

Kick plate adjustable depth: 30-94 mm



Safety & Maintenance

Aqua Safe™

Kid Safe™ - panel

Rinse-aid indication: Notification in display

Technical data

Size: 3/4" Can be connected to hot or cold water

Max. temperature of inflow water: 70 °C

Noise level: 44 dB(A)re 1 pW

Reference program: 1

Total cycle time of reference program (min): 169 min

Estimated yearly energy consumption: 295 kWh

Energy consumption reference program: 0,78 kWh

Energy stars: 3,5

Water stars: 5

Water consumption: 12,2 l

Consumption in off mode: 0,5 W

Consumption in standby mode: 2 W

Connection rating: 2000 W

Voltage: 220-240 V

Current: 10 amp

Frequency: 50 Hz

Required inlet water pressure: 0,03-1 MPa

Net weight: 45,2 kg

Dimensions

Product dimensions (HxWxD): 81,9 x 59,6 x 55,9 cm

Length electrical cord: 1,825 m

Depth with door open: 1198 mm

Length inlet hose: 163 cm

Length outlet hose: 200 cm

Logistic information

Dimensions of packed product (HxWxD): 89 x 64 x 68 cm

Gross weight: 48,5 kg

Product code: 732366

EAN code: 3838782179167