Split System

Specifications





Kelvinator

Split System

Specifications



Model		KSD25HRH	KSV25HRH	KSD35HRH	KSV35HRH	KSD50HRH	KSV50HRH	KSD71HRH	KSV71HRH	KSD90HRH	KSV90HRH	KSV25CRH	KSV35CRH	KSV71CRH
Category		Inverter	Inverter	Inverter	Inverter	Inverter	Inverter	Inverter	Inverter	Inverter	Inverter	Inverter	Inverter	Inverter
Туре		Reverse cycle	Reverse cycle	Reverse cycle	Reverse cycle	Reverse cycle	Reverse cycle	Cooling only	Cooling only	Cooling only				
	Min	1.0	1.0	1.4	1.4	2.0	2.0	2.8	2.8	3.6	3.6	1.0	1.4	2.8
Cooling Capacity (kW)	Rated	2.5	2.5	3.5	3.5	5.0	5.0	7.1	7.1	9.0	9.0	2.5	3.5	7.1
	Max	2.8	2.8	3.9	3.9	5.5	5.5	7.8	7.8	9.9	9.9	2.8	3.9	7.8
	Min	1.3	1.3	1.6	1.6	2.4	2.4	3.2	3.2	4.1	4.1	NA	NA	NA
Heating Capacity (kW)	Rated	3.2	3.2	4.0	4.0	6.0	6.0	8.0	8.0	10.0	10.0	NA	NA	NA
	Max	3.5	3.5	4.4	4.4	6.6	6.6	8.8	8.8	11.0	11.0	NA	NA	NA
Cooling AEER		4.79	4.79	4.26	4.26	4.02	4.02	3.56	3.56	3.51	3.51	4.79	4.26	3.56
Heating ACOP		4.76	4.76	4.29	4.29	4.02	4.02	3.50	3.50	3.50	3.50	NA	NA	NA
Outdoor unit dimensions (W x H x D)	(mm)	885 x 554 x 365	924 × 702 X 382	924 × 702 X 382	924 × 702 X 382	924 x 702 X 382	1040 × 810 × 455	1040 x 810 x 455	885 x 554 x 365	885 x 554 x 365	924 × 702 X 382			
Indoor unit dimensions (W x H x D)	(mm)	802 x 297 x 189	1080 x 335 X 226	1259 x 362 x 282	1259 x 362 x 282	802 x 297 x 189	802 x 297 x 189	1080 x 335 x 226						
Weight outdoor unit	(kg)	33.2	32.5	33.2	32.5	43.2	43.2	52.5	51.8	64.5	64.5	32.5	32.5	51.8
Weight indoor unit	(kg)	9.3	9.3	9.3	9.3	14.5	14.5	14.5	14.5	19.5	19.5	9.3	9.3	14.5
Running current	(A)	2.9	2.9	4.1	4.1	6.5	6.5	9.9	9.9	12.6	12.6	2.3	3.6	8.7
Maximum current	(A)	9.5	9.5	10.5	10.5	15.5	15.5	17.5	17.5	19.5	19.5	9.5	10.5	17.5
Power supply connection point		Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Wires between indoor & outdoor units		4	4	4	4	4	4	4	4	4	4	4	4	4
DRED enabled		Yes	No	Yes	No	Yes	No	Yes	No	Yes	No	No	No	No
Indoor air circulation (silent/low/medium/high/turbo)	(L/s)	78/97/131 /147/167	78/97/131 /147/167	78/97/131 /147/167	78/97/131 /147/167	161/197/228 /286/333	161/197/228 /286/333	161/203/231 /294/325	161/203/231 /294/325	183/268/304 /377/425	183/268/304 /377/425	78/97/131 /147/167	78/97/131 /147/167	161/203/231 /294/325
Gas pipe size	(mm)	9.52 (3/8")	9.52 (3/8")	12.70 (1/2")	12.70 (1/2")	12.7 (1/2")	12.7 (1/2")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	9.52 (3/8")	12.70 (1/2")	15.88 (5/8")
Liquid pipe size	(mm)	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	6.35 (1/4")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	6.35 (1/4")	6.35 (1/4")	9.52 (3/8")
Maximum piping length vertical	(m)	10	10	10	10	20	20	25	25	25	25	10	10	25
Maximum piping length	(m)	25	25	25	25	30	30	50	50	50	50	25	25	50
Refrigerant		R32	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32	R32
Refrigerant weight	(g)	830	830	900	900	1450	1450	1600	1600	2700	2700	830	900	1600
Precharge pipe length	(m)	5	5	5	5	5	5	5	5	5	5	5	5	5
Additional refrigerant required over precharge pipe length	(g/m)	15	15	15	15	15	15	30	30	30	30	15	15	30
Indoor sound pressure high setting	(dBA)	42	42	42	42	49	49	50	50	55	55	42	42	50
Indoor sound pressure low setting	(dBA)	25	25	25	25	32	32	33	33	33	33	25	25	33
Outdoor sound pressure	(dBA)	56	56	56	56	60	60	63	63	63	63	56	56	63
Outdoor sound power	(dBA)	60.5	60.5	59.4	59.4	64.1	64.1	65.0	65.0	67.4	67.4	60.5	59.4	65.0
Moisture removal	(L/h)	1.0	1.0	1.2	1.2	1.9	1.9	2.4	2.4	3.0	3.0	1.0	1.2	2.4
Ambient temperature minimum	(°C)	-15	-15	-15	-15	-15	-15	-15	-15	-15	-15	0	0	0
Ambient temperature maximum	(°C)	50	50	50	50	50	50	50	50	50	50	50	50	50
Energy star rating cooling		5.0	5.0	4.0	4.0	3.5	3.5	2.5	2.5	2.5	2.5	5.0	4.0	2.5
Energy star rating heating		5.0	5.0	4.0	4.0	3.5	3.5	2.5	2.5	2.5	2.5	NA	NA	NA
Warranty	(years)	5	5	5	5	5	5	5	5	5	5	5	5	5





installation information, have your retailer

Customer care

telephone: 1300 363 640

13 13 49 for the cost of a local call (Australia only).

Spare parts

please call 13 13 50 for the cost of a local call.

Kelvinator. We are part of the Electrolux Family. To add a touch of professional inspiration to your home, visit electrolux.com.au

Warranty
Electrolux Home Products Pty Ltd and Electrolux (NZ) Limited (collectively Electrolux) warrants that for domestic applications the Appliances featured in this brochure are free from defects in materials and workmanship for 5 years, and warrants that for featured accessories a period of 12 months, following the date of original purchase and subject to the conditions set out in the warranty card accompanying the product when purchased. This warranty is in addition to the other rights and warranties you may have under the Australian Consumer Law (ACL) and Electrolux will at all times comply with its obligations at law including the ACL. For New Zealand customers Electrolux will at all times comply with its obligations pursuant to law including the Consumer Guarantees Act, the Sale of Goods Act and the Fair Trading Act. Where appliances are purchased in NZ for commercial purposes the Consumer Guarantees Act does not apply.

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous product development, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes the products that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Electrolux will at all times comply with its obligations pursuant to law. Colours of products illustrated are as close as printing limitations allow.