

iQ700 LC91BD552A 90 cm Wall Mounted Canopy Rangehood



The wall-mounted canopy rangehood with high extraction rate – adds a sleek design element your kitchen.

- ✓ The highly efficient 810 m³/h extraction rate provides ideal air quality in the kitchen.
- ✓ The energy saving LED lighting with dimmer function ensures ambient lighting and optimal visibility when cooking.
- ✓ Quiet at 59 dB at level 2 (430 m³/h) - 150mm ducted.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert to previous setting after 6 min.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 22.0
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 610
 Boost position output recirculating (m³/h) : 480
 Maximum output recirculating air (m³/h) : 400
 Boost position air extraction (m³/h) : 810
 Number of lights : 3
 Noise level (dB) : 66
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable stainless steel
 EAN code : 4242003695937
 Connection Rating (W) : 269
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : AU plug
 Installation typology : Wall-mounted



4 242003 695937

Optional accessories

LZ57300	cleanAir Recirculation Kit
LZ56200	CleanAir active carbon filter spare part
LZ53451	Active carbon filter
LZ53450	Recirculating kit

iQ700

LC91BD552A

90 cm Wall Mounted Canopy Rangehood

Features

Design & Innovation

- 90 cm wall installation/ceiling mounted(instal Decorative Hood
- slimLine design
- 3 x 3 Watt LED Lights

Convenience

- Wall mounted hood
- 3 power levels + 2 intensive levels
- softLight with dimming function
- Electronic controls with low-lift push buttons
- Boost function
- climateControl sensor automatically adjusts the rangehood power level to the steam and odours
- lightControl white LED control panel
- metal grease filters with stainless steel cover
- iQ Drive BLDC brushless motor
- Saturation display for filters

Power and Mode of Operation

- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 610 m³/h
Intensive 810 m³/h
- Automatic run on - 10 min
- Intensive operation automatic revert - 6min
- Top Automatic EE
- 3 power levels + 2 intensive levels
- Twin channel high performance fan motor
- Rim ventilation
- Suitable for ducted and re-circulating operation
- Intermittent ventilation function

Cleaning

- Dishwasher safe metal grease filters

Safety and Quality

- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
Max. normal use: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
Intensive: 72 dB(A) re 1 pW (58 dB(A) re 20 µPa sound pressure)
- Sound insulation mats for optimised sound absorption

Dimensions (HxWxD)

- Power rating: 269 W
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Appliance - Recirculated with cleanAir module (HxWxD):
689 x 900 x 500 mm
- Accessories required for recirculation mode: CleanAir Module
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)

iQ700

LC91BD552A

90 cm Wall Mounted Canopy
Rangehood

Dimensioned drawings

