

V-ZUG Australia Pty. Ltd 2/796 High Street East Kew Vic 3102, VICTORIA/Australia Phone +61 (03) 9832 7500 enquire.au@vzug.com, www.vzug.com

# Brochure DH-L8 / 11



# Selected product

Article no.: 6400260003EAN code: 7640151575168

- Controls: dial

Standard width: 110 cmFront design: Stainless steel

- Installation method: integrated range hood



# Details DH L11

## Design

- Controls: dial

- Standard width: 110 cm

- Front design: Stainless steel

- Installation method: integrated range hood

#### **Dimensions**

- Appliance height: 300 mm

- Front height: 300 mm

- Height: Extracted air/recirculation air: 30 cm

Appliance width: 110 mmAppliance depth: 300 mm

- Max. appliance depth: 300 mm

- Max. appliance depth. 300 h

- Empty weight: 29 kg

## Display and operation

- Controls: dial

- Fan power level display

- Lighting: LED

- Number of lights: 4

#### **Energy**

- Energy efficiency rating: C

- Annual energy consumption: 90.8 kWh

- Lighting efficiency rating: A

- Fluid dynamic efficiency: 22.9

- Fluid dynamic efficiency rating: C

- Type of connection (1): 220-240 V~

- Nominal lighting output (quantity x W): 4 x 3

- Frequency (1): 50-60 Hz

- Connected loads (1): 0.2 kW

- Fuse protection (1): 10 A

- Plug type: Schuko 16A

- Plug type B: AS/NZS 3112

- Connection cable: 1.5 m

## Range hood features

- Grease filter cleaning indicator

- Power levels: 3 + i

- Fleece grease filter: 1

- Side exhaust

- Non-return flap, integrated/attached: included

#### **Functions**

- Extracted air

- Grease filter cleaning indicator

- Side exhaust

- Intensive setting

- Automatic after-running time

#### **Additional data**

- Exhaust air connection (diameter): 150 mm

- Lighting efficiency: 32

- Illumination on cooking surface: 382 lux

- Grease absorption capacity rating: E

- Extracted air output, intensive setting: 563 m³/h

- Extracted air output, max. setting: 469 m<sup>3</sup>/h

- Extracted air output, min. setting: 228 m<sup>3</sup>/h

- Recirculation air output, intensive setting: 322 m³/h

- Recirculation air output, max. setting: 233 m<sup>3</sup>/h

- Recirculation air output, min. setting: 146 m³/h

- Extracted air noise output, intensive setting: 61 dB(A)

- Extracted air noise level, max. setting: 57 dB(A)

- Extracted air noise output, min. setting: 40 dB(A)

- Motor(s): 1

- Motor output: 188 W

- Feature level: 3

#### Preisschild Dunstabzüge

- Extracted air

- Side exhaust

- Fleece grease filter: 1

- Grease filter cleaning indicator



# Service and interfaces

- Warranty: 2 years