







Product Detail

Model Number X7P04S (Stainless Steel Finish) Special Order

Hood Mounting Island Mounted Canopy

Cooking Coverage Suits 30cm - 60cm Cooking Surfaces

Filtration S-Flow Baffle Filters 1x (H-25) - Dishwasher Safe

Lighting LED 2x (Warm White 1.0W)

Finish AISI304 1.0mm Food Grade Stainless Steel

Controls LED Backlit 4 Button mastermind Electronic Control

with LED Speed Indicator

Speed Settings 3 Speed + Boost Mode

Timer Function Programmable Timer (10min Increments)

Auto fan shut off after 2-hours of inactivity

Outlet Top Duct Outlet

Ducting (Remote) Dia. 200mm Acoustic Flexi Ducting - Five (5) Meter Length

(Supplied)

Ducting (On Board) Optional On Board Motor Ducting Kits Available

Power Motor - Dia. 150mm (Recommended)

Hood Width 360mm
Hood Depth 360mm

Hood Height (Fascia) 800mm (standard) - Custom Height Available - 400mm (min)

Installation Height 700 - 750mm* (Recommended)

600mm* (Minimum)
*Clearance above the highest point of the cooktop to the underside of hood










Filtration Zone

Dimensioned Drawing





Whispair Endurance Warranty







5 YEAR WARRANTY

Your Hood. Your Colour. Your Way.

Available Finishes







Available Models - Select Your Motor Solution & Optional Finish

Stainless Steel Finish - Special Order

On Board

X7P04S5.0P (/T) Power 1,020m³/hr (Top Ducted) SPL: 53.9dB(A)

Remote External (Roof or Wall Mounted)

X7P04S5.EL Lite 800m³/hr SPL: 43.8dB(A) In / 52.7dB(A) Out X7P04S5.EP Pro 1,140m³/hr SPL: 52.6dB(A) In / 58.5dB(A) Out

Remote Inline (Through Wall or Eave)

X7P04S5.IL Lite 800m³/hr SPL: 39.3dB(A) In / 52.7dB(A) Out X7P04S5.IP Pro 1,140m³/hr SPL: 49.6dB(A) In / 58.5dB(A) Out

X1FP.010* Height Extension - Plus 100mm

*Additional charges apply

SPL - Nominal Sound Pressure Level on Boost (Max) Speed