

V-ZUG Ltd

Industriestrasse 66, P.O.Box 59, 6301 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure GK56TIMS



Selected appliance

- Article no.: 89A367
- Short designation: GK56TIMS
- Frame: Bevelled edge

Also available with/as (*)

- Frame Flush-fitting, Chrome standard frame

(*) Not all combinations are available. Ask your retailer for advice.

Details GK56TIMS

Design

- Frame: Bevelled edge

Dimensions

- Appliance height: 55.0 mm
- Appliance width: 910.0 mm
- Appliance depth: 514.0 mm
- Appliance corner radius: 8.0 mm
- Support size width: 886.0 mm
- Max. support size width: 886.0 mm
- Support size depth: 490.0 mm
- Max. support size depth: 490.0 mm
- Installation height when surface-mounted: 51.3 mm
- Cut-out width when surface-mounted: 886.0 mm
- Max. cut-out width when surface-mounted: 886.0 mm
- Cut-out depth when surface-mounted: 490.0 mm
- Max. cut-out depth when surface-mounted: 490.0 mm
- Empty weight: 18.5 kg
- Cooking zone 1 dimensions: 18x20 cm
- Cooking zone 2 dimensions: 18x20 cm
- Cooking zone 3 dimensions: 28 cm
- Cooking zone 4 dimensions: 18x20 cm
- Cooking zone 5 dimensions: 18x20 cm

Display and operation

- Display: digital display
- Controls: MultiSlider/direct selection
- Slider control
- Operating time / switch-off time
- Button sound (on/off)

Energy

- Cooking zone 1 max. power: 3700.0 W
- Cooking zone 2 max. power: 3700.0 W
- Cooking zone 3 max. power: 3700.0 W
- Cooking zone 4 max. power: 3700.0 W
- Cooking zone 5 max. power: 3700.0 W
- Type of connection: 220-240 V~

- Frequency (1): 50/60 Hz
- Connected loads: 11.1 kW
- Plug type: cable

Hob features

- Powerplus: 5.0
- Hob category: Induction
- Operating time with shut-down function
- Residual heat indicator
- Timer
- Restore function
- Cooking zones: 5
- Heating technology: induction cooking zones

Functions

- Pause button
- Warming function
- Automatic warm-up function
- Cleaning lock
- Zone connection
- Melt function
- Simmer function
- Childproof lock
- Safety package
- Pan detection (10–22 cm)

Service and interfaces

- Warranty: 2 years