

MDR-ZX600/BLK

Multi Layer diaphragms

High quality large driver units accurately reproduce a broad, dynamic frequency range.

High Energy Neodymium Drivers

Efficient Neodymium drivers reproduce clear mid-range and low-end sound.

Pressure Relieving Earpads

Take the discomfort out of the equation and enjoy your extended music sessions in comfort.

Rugged Y-Type Cord

A rugged Y-type design makes for a tangle-free experience.

Specifications

Audio

Driver Unit	40 mm, dome type (CCAW Voice Coil)
Frequency Response	6 - 25,000Hz
Impedance	40 ohms at 1 kHz
Sensitivity (db)	104 dB/mW

General

Design	Over-the-head, Monitor
Diaphragm	PET
Headband	Wide, Adjustable
Magnet	Neodymium
Plug	Gold-plated, L-shaped stereo mini plug
Type of Use	Portable, Home, Studio

Hardware

Cord	Oxygen-Free Copper; Single-sided
Headphone Type	Closed supra-aural, Dynamic

Power

Power Handling Capacity	1000 mW
-------------------------	---------

Weights and Measurements

Cord Length (Approx.)	47 1/4 in (1.2 m)
Weight (Approx.)	170 g (6 oz)

Accessories

Supplied Accessories	Operating Instructions (1)
----------------------	----------------------------