

Datasheet DI-SE



 Article number: V077366_Abluft_Standard

Selected features

Width: 120 cm

Fan: Extracted air

Front design: Stainless steel

Telescopic casing: Standard

Installation method: Island hood

Also available with/as (*)

- Width: 100 cm

- Telescopic casing: Medium

(*) Not all combinations are available. Ask your retailer for advice.

Details DI-SE

Range hood features

- Metal grease filter: 3
- Extracted air
- Forced convection with long-life activated charcoal filter
- Forced convection with standard activated charcoal filter
- Halogen spotlights: 4.0
- Intensive setting
- Grease filter cleaning indicator
- Connection for fresh air/exhaust air flap
- Power levels: 4
- of which: number of intensive levels: 1
- Fan power level display
- Air delivery rate: 550.0 m³/hr
- Static pressure: 464.0 pascal
- Motor(s): 1
- Motor output: 175.0 watt
- 2-duct radial fans
- Electronic control
- Noise emission: 44 dB
- Good grease absorption
- Easy to clean and operate
- Grease filter can be washed in the dishwasher
- Exhaust air connection (diameter): 150.0 mm

Service and interfaces

- Warranty: 2 year(s)

Energy

- Voltage: 230 volt
- Connected loads: 0,255 kilowatt
- Fuse protection: 10 ampere

Dimensions

- Appliance width mm: 1200
- Appliance depth mm: 600
- Empty weight: 24.0 kg