QUICK REFERENCE GUIDE > WB60SDEX2

# Warming Drawer, 60cm

Series 9 | Contemporary

Stainless Steel



Keep plates warm until ready to serve; rapid proof or slow cook to perfection. Pair with an oven for matching Contemporary design.

- A companion product, designed to match with other Contemporary style Fisher & Paykel products
- Space to keep six standard-sized place settings evenly warm
- Easy to clean smooth-glass base
- Six versatile tailored programmes for warming, proofing, dehydrating and slow cooking

# **DIMENSIONS**

Height	140 mm
Width	596 mm
Depth	567 mm

# **FEATURES & BENEFITS**

## Complementary design

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

# Multi-function flexibility

Choose from six tailored functions including Rapid Proof, Dehydrate and Slow Cook.

# Easy to clean

<>

#### Easy to use

Handle-free, push-to-open with capactive touch controls, our Tall Warming Drawer comes with a built-in accessory rack for optimising space.

### Precise control

With fast and even heating, our warming drawer is great for keeping food warm and low temperature cooking, as well as resting after a traditional roast in the oven and proofing dough.

#### Safe and sound

With Automatic switch-off and Delayed start functionality, our warming drawers help keep dishes warm until it is time to serve the main meal.

# **SPECIFICATIONS**

# Capacity

Cappuccino cups	20
Espresso cups	42

Maximum allowable weight	25kg
Place settings	6
Usable depth	408mm
Usable height	98mm
Usable width	535mm

#### Cleaning

Easy clean smooth-glass base

#### Controls

Audio feedback	
Automatic pre-set	
Automatic timers	30', 45', 1h, 2h, 4h, 6
Delayed start	
Interior light	LE
Intuitive capacitive touch	
On/Off indicator	
Pre-set heating functions	
Push-to-open drawer	
Sabbath mode	
Standby mode	

# **Functions**

Cups

Dehydrate

Number of functions

Plates

Rapid proof

Slow cook

Warm

QUICK REFERENCE GUIDE > WB60SDEX2

Performance		
Heated glass base and fan	•	
Low temperature cooking	•	
Temperature levels	6	
Temperature range	35°C-85°C	

Power requirements

Amperage 10A

Maximum power 810W

Power cord length 1800mm

Power outlet 3-prong grounding-type

Supply frequency 50/60Hz

Supply voltage 220-240V

**Product dimensions** 

Adjustable front door panel to

Depth 567 mm

Height 140 mm

Width 596 mm

Safety

Automatic turn off after 12
Full extension telescopic

Warranty

Parts and labour 2 years

SKU 82107

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

# Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty Booklet



Installation Guide

