

MOVE

Version

Slide-out 90 cm - white

Collection

DESIGNER SERIES - Design



*The photograph is purely for information
It may not correspond to the selected version.*

FEATURES

Scotch-Brite stainless steel (AISI 304)
Lower part in white tempered glass
Sliding door
Electronic controls
LED lighting
Metallic grease filter, removable and washable
Optional regenerable Carbon.zeo filter
Rear-ducting possible
Optional chimney
Optional glass shelf

Special order

OPTIONAL ACCESSORIES

KACL.934
Carbon.Zeo filters
KACL.815
Protective cleaning cloths for stainless steel (box 10 pcs)
IN950
Remote under-roof motor 950 m³/h
KACL.770#41F
Remote under-roof 1100 m³/h Brushless
KACL.786#41F
Outdoor extractor fan 1000 m³/h
EW1500
Outdoor extractor fan 1500 m³/h
EW1300
Remote under-roof motor 1300 m³/h

TECHNICAL FEATURES

Installation type
Built-in
Dimensions
90 cm
Finishing
Scotch brite stainless steel (AISI 304)
 Lower body: finished in black tempered glass
Motor
800 m³/h
Type of control
Electronic controls
Speed settings
4
Lighting
LED 3x1.2 W - 3200 K
Filter
Metallic filter "Base" - 198x161 mm - 2 pz
Charcoal filter
Carbon.Zeo filters
Minimum distance
Gas hob: 52 cm
Electric hob: 52 cm

PACKAGING: WEIGHTS AND VOLUMES

Gross weight
20 kg
Net weight
17 kg
Volume
0,18 m³
Packaging size
Length
995 mm
Height
465 mm
Depth
395 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption
280 W
Current
220-240V
Frequency
50-60Hz
Plug type
Shuko

MOTOR TECHNICAL SHEET


Maximum capacity
680 m³/h
I.E.C. 61591
Maximum sound level
68 dB(A)re1pW
I.E.C.60704-2-13
Maximum pressure (Pa)
500 Pa
Maximum motor power
215 W

MOVE


Version
Slide-out 90 cm - white

Collection
DESIGNER SERIES - Design


Hood and rear view



Optional chimney



Optional shelf



MOVE

Version
Slide-out 90 cm - white

Collection
DESIGNER SERIES - Design

MOTOR TECHNICAL SHEET

Speed motor	1	2	3	4
Sound level dB(A)re1pW-I.E.C.60704-2-13	49	56	62	68
Capacity (m3/h) I.E.C.61591 Standardised ducting	280	370	480	680
Maximum pressure (Pa)	390	420	480	500
Power motor (W)	132	153	175	215
Air outlet	150	150	150	150

CAPACITY / PRESSURE

