

DBI253IB.BS

General description

Turbo Drying™ - Fan assisted moist air extraction

Classic

Installation type: Built under work top

Size: XL, 82 cm

Number of baskets: 3

15 place settings

8 Steel, SCS+

Top cutlery tray: Top Tray with Instant Lift™; Top Tray with Instant Lift™; Rack for knives (top); Rack for bowls (top); Telescopic rails for top tray; Handle (top)

Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support

Lower rack type: Premium - foldable pin rows

Construction & Performance

Exterior float

8 Steel™ construction

Hidden heater

SCS+ (Super Cleaning System+)

Number of spray arms: 3

Number of spray zones: 9

Use & Flexibility

Number of place settings: 15 place settings

Number of baskets: 3

Top cutlery tray: Top Tray with Instant Lift™; Top Tray with Instant Lift™; Rack for knives (top); Rack for bowls (top); Telescopic rails for top tray; Handle (top)

Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable glass support

Easy sliding telescope rails with ball bearings for the upper basket

Lower rack type: Premium - foldable pin rows

Dense basket wiring in both upper and lower basket

Required inlet water pressure: 0,03-1 MPa

Interaction & Control

Display type: LCD display

Customizable programs: Program memory

Number of programs: 7

Programs, options and modes

7 programmes: Quick wash; Intensive programme; Eco wash; Hygiene wash; Time program; Heavy wash; Rinse and hold

Delayed start: Variable start delay up to 24 hours

Multi tablet function

Super rinse

Time set

Speed mode

Night mode

Extra dry

High temperature

Super rinse

Design & Integration

From front adjustable rear foot

Water connection: Size: 3/4" Can be connected to hot or cold water

Depth (incl. wall spacing): 560 mm

Height setting: 50 mm


Kick plate adjustable depth: 30-94 mm

Safety & Maintenance

Aqua Safe™

Kid Safe™ - panel

Rinse-aid indication: Notification in display



Technical data

Size: 3/4" Can be connected to hot or cold water

Max. temperature of inflow water: 70 °C

Noise level: 44 dB(A)re 1 pW

Reference program: 1

Total cycle time of reference program (min): 169 min

Estimated yearly energy consumption: 295 kWh

Energy consumption reference program: 0,78 kWh

Energy stars: 3,5

Water stars: 5

Water consumption: 12,2 l

Consumption in off mode: 0,5 W

Consumption in standby mode: 2 W

Connection rating: 2000 W

Voltage: 220-240 V

Current: 10 amp

Frequency: 50 Hz

Required inlet water pressure: 0,03-1 MPa

Net weight: 44,5 kg

Dimensions

Width: 596 mm

Height: 819 mm

Depth: 559 mm

Length electrical cord: 1825 mm

Depth with door open: 1198 mm

Length inlet hose: 163 cm

Length outlet hose: 200 cm

Logistic information

Packaging width: 640 mm

Packaging height: 890 mm

Packaging depth: 680 mm

Gross weight: 47,8 kg

Product code: 732488

EAN code: 3838782326851