

V-ZUG Ltd

Industriestrasse 66, P.O.Box 59, 6301 Zug/Switzerland

Phone +41 58 767 67 67, Fax +41 58 767 61 67

info@vzug.com, www.vzug.com

Brochure DSTS



Selected appliance

- Article no.: 6400465005
- Short designation: DSTS9g
- Standard width: 90.0 cm
- Extracted air
- Front design: Glass
- Installation method: downdraft

Also available with/as (*)

- recirculation air Yes
- Recirculation air filter Standard chargoal filter, Long-life activated charcoal filter

(*) Not all combinations are available. Ask your retailer for advice.

Details DSTS9g

Additional settings

- Clean air function

Design

- Standard width: 90.0 cm
- Extracted air
- Front design: Glass
- Installation method: downdraft

Dimensions

- Appliance height: 650.0 mm
- Appliance width: 880.0 mm
- Appliance depth: 120.0 mm
- Max. appliance depth: 120.0 mm
- Empty weight: 35.0 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 1
- Grease filter cleaning indicator

Energy

- Energy efficiency rating: B
- Annual energy consumption: 62.1 kWh
- Lighting efficiency rating: A
- Fluid dynamic efficiency: 27.1
- Fluid dynamic efficiency rating: B
- Type of connection: 220-240 V~
- Nominal lighting output (quantity x W): 1 x 6 W
- Frequency (1): 50 Hz
- Connected loads: 0.276 kW
- Fuse protection: 10.0 A
- Plug type: AS/NZS 3112
- Connection cable: 1.5 m

Range hood features

- Remote control: No

- Dimmable light
- Fleece grease filter: 2
- Non-return flap, integrated/attached: included

Functions

- Intensive setting
- Automatic after-running time

Additional data

- Exhaust air connection (diameter): 150.0 mm
- Lighting efficiency: 28.1
- Illumination on cooking surface: 170.0 lux
- Grease absorption capacity rating: D
- Extracted air output, intensive setting: 670 m³/h
- Extracted air output, max. setting: 420 m³/h
- Extracted air output, min. setting: 280 m³/h
- Extracted air noise output, intensive setting: 69.0 dB(A)
- Extracted air noise level, max. setting: 57.0 dB(A)
- Extracted air noise output, min. setting: 49.0 dB(A)
- Recirculation air output, intensive setting: 670 m³/h
- Recirculation air output, max. setting: 330 m³/h
- Recirculation air output, min. setting: 155 m³/h
- Motor(s): 1
- Motor output: 270 W
- Feature level: 5

Service and interfaces

- Warranty: 2 years