

DFI654B

General description

Turbo Drying™ - Fan assisted moist air extraction

Installation type: Fully integrated

Size: XL, 82 cm Number of baskets: 3

15 place settings 8 Steel™ Construction, SCS+ (Super Cleaning System+)

Cutlery Flexi Tray with Instant Lift™

Upper rack type: Premium - two foldable wine shelves, fixed pin rows and one foldable

alass support

Lower rack type: Premium - foldable pin rows

Cutlery basker

Construction & Performance

8 Steel™ construction

Hidden heater

SCS+ (Super Cleaning System+)

Sensi Clean™ Sensor - detects the dirtiness level

Number of spray arms: 3

Number of spray zones: 9

Jet Spray[™] - extra dishwashing power for tall objects Wide Spray[™] - extra washing power for pots and pans

Power Zone™ for the cutlery basket

Use & Flexibility

15 place settings

Basket class: Premium

Number of basket levels: 3

Cutlery Flexi Tray with Instant Lift™

Height adjustable upper basket

Easy sliding telescope rails with ball bearings for the upper basket Dense basket wiring in both upper and lower basket

Easy-to-use cutlery basket

Interaction & Control

Display type: LCD display

Program names in full text Number of programs: 13

Number of options: 4

Delayed start: Variable start delay up to 24 hours

Display and sound feedback settings

Programs, options and modes

13 programs: Auto wash; Eco wash; Hygiene wash; Time program; Plastic wash; Heavy wash; Rinse and hold; Sanitation wash; Upper half wash; Lower half wash; Crystal glass; Quick Pro wash; Self-cleaning

High temperature

Extra dry

Variable start delay up to 24 hours

Super rinse

Time set Green mode

Speed mode

Night mode

Intensive mode

Design & Integration

Kick plate adjustable depth: 30-94 mm From front adjustable door spring From front adjustable rear foot

Integrated anti-siphon device

Niche dimensions (HxWxD): 82 × 60 × 56 cm

Safety & Maintenance

Agua Safe™

Kid Safe™ - panel

Rinse-aid indication: Notification in display

Stand by water protection

Exterior float

Anti block drain pump



Size: 3/4" Can be connected to hot or cold water

Max. temperature of inflow water: 70 °C

Noise level: 42 dB(A)

Reference program: 1

Total cycle time of reference program (min): 170 min

Estimated yearly energy consumption: 295 kWh

Energy consumption reference program: 0,79 kWh

Energy stars: 3,5 Water stars: 5

Water consumption: 12,2 I Consumption in off mode: 0,49 W Consumption in standby mode: 0,49 W

Connection rating: 2000 W Voltage: 220-240 V

Current: 10 amp

Frequency: 50 Hz

Required inlet water pressure: 0,03-1 MPa

Net weight: 47 kg

Yes

Dimensions

Product dimensions (HxWxD): 81,9 × 59,6 × 55,9 cm

Depth with door open: 1198 mm Length electrical cord: 1,825 m Length inlet hose: 163 cm Length outlet hose: 200 cm

Logistic information

Dimensions of packed product (HxWxD): $89 \times 64 \times 68$ cm

Gross weight: 50.3 kg

Product code: 729063