

V40 SERIES

UNDERBENCH INSTALLATION INSTRUCTIONS

1. Cabinet dimensions:

Height 820mm – 860mm (40mm adjustable feet)

Width 595mm

Depth 571mm

2. This cabinet is not designed to be fully integrated behind a joinery door.
3. Please note that a minimum cut out of 615mm is required to facilitate installation, removal and servicing.
4. This cabinet requires 10mm clearance on both sides and top, 40mm clearance at the rear. A ventilation grid must be installed in the 40mm clearance at the rear (either in the sides, top or back of the joinery). Minimum grid size is 200mm x 40mm.
5. This cabinet is front venting. The cabinet draws air from the rear and expels through the grille under the door at the front. If a kick board is to be placed in front of the ventilation grill at the front a grill must be fitted in to the kick board with a minimum air flow allowance of 150cm².
6. This cabinet has a power switch located on the control panel so power point location is not critical.
7. This cabinet requires a standard 240 volt/10 amp power point.
8. The power cord is 1.9m in length and is fixed on the right side at the back when looking from front of cabinet.
9. As with most appliances of today, this cabinet has sensitive electronic components which are susceptible to damage through lightning and electricity supply faults. It is therefore advised to use a power surge protector to avoid problems of this nature.
10. Please see below detailed dimensional diagrams. Please note: The diagram below is for the 85mm plinth recess version.

