



Model		HSA35R
Indoor unit		HSA35R-I
Outdoor unit		HSA35R-O
Type		Reverse cycle
Rated values		
Cooling Capacity	W	3500
Heating Capacity	W	4000
Rated Input-Cooling	W	805
Rated Input-Heating	W	920
Moisture Removal	Litre/Hour	1.2
Air Circulation	m ³ /h	620
EER		4.35
COP		4.35
AEER		4.26
ACOP		4.26
Energy star rating for cooling		4
Energy star rating for heating		4
Refrigerant	Type	R32
Noise		
Indoor unit (fan mode high)	dB (A)	41
Indoor unit (fan mode silent)	dB (A)	25
Outdoor unit	dB (A)	61.5

Power Supply		
Voltage, Frequency, Phase		220-240V/50Hz-1Ph
Rated current cooling	A	3.6
Rated current cooling	A	4.1
Locked rotor current	A	
Maximum input power [c / h]	W	1200/1300
Maximum input current	A	7.3/7.9
System		
Compressor type		Rotary
Expansion Device		Capillary
Evaporator		Copper tube and Aluminum Fin
Condenser		Copper tube and Aluminum Fin
Piping		
Liquid pipe	inch	1/4
Gas pipe	inch	3/8
Maximum piping length/ height	m	25/10
Features		
Transparent temperature display		Yes
LCD Wireless Remote Controller		Yes
Washable PP Filter		Yes
Silver Ion filter		Yes
24 Hours Timer		Yes
5 Speed and Auto mode for indoor fan control		Yes
Omnidirectional Air Flow		Yes
Dimmer		Yes
Sleep Operation		Yes
Smart Mode		Yes
Super Function		Yes
Demand Response		No
Auto Restart		Yes
Dimensions		
Net dimensions indoor unit	[WxHxD] mm	815×270×212
Net dimensions outdoor unit	[WxHxD] mm	810x585x280
Net weight indoor unit	kg	8.5
Net weight outdoor unit	kg	33
Packing dimensions indoor unit	[WxHxD] mm	870×335×265
Packing dimensions outdoor unit	[WxHxD] mm	940x630X385
Gross weight outdoor unit	kg	11
Gross weight indoor unit	kg	36