



HYDROTAP G5 BCS ELITE BRUSHED GOLD

 **BOILING**

 **CHILLED**

 **SPARKLING**

FILTERED

Order Code H54783Z07AU

Zip HydroTap Design Range Boiling, Chilled, Sparkling, Filtered water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, SteriTouch® antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and 2 disposable CO2 cylinders.



Manufacturing Code	H54783Z07AU
Capacity	Residential

Tap	Zip HydroTap Design Range ELITE Tap (Brushed Gold)
Water Pressure	Min 250kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.53kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W339mm x D460mm x H333mm
Product Approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

'1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.3. HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com'

BKL2 HydroTap G5 v1.00 02.21 BCS BCS20

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Clearance envelope

Position the Tap and the Command Centre as close together as possible.

200
333
50
Command Centre width 50

HydroTap Tap options

Classic Plus

116
116
216
126
46

Elite Plus

110
110
221
135
46

Font options

Raised Font with 135mm Extension

116
116
280
351
268
20
219

Font with 135mm Extension

116
116
280
351
104
6
219

Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap

Sink

Air outlet louvre (if required)
Cut-out in door/wall, towards the top of the cabinet

285
60
43

Air inlet cut-out (required)
Cut-out in cabinet floor

326
43

Clearance envelope

200
333
50
Command Centre width 50

HydroTap G5 BCS Home

shown with "Classic Plus" Tap

4mm buffer pad air space

Classic Plus Tap

216
116
126
46
35
108
35
10
164
116
104
60
219
10
35
108
35
10

Clearance Envelope

CO₂ gas cylinder

380
200 min.
333
50 min.
339
50 min.
460

Mains cold water isolation valve (not supplied)

Air inlet grille

IEC Flex & Plug 230-240V, 50Hz power outlet

SCALE 1:5

ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

