

installation accessory
HZ9VRUD0



Features

Technical Data

Dimensions of the packed product (HxWxD) (mm) : 94 x 250 x 281

Pallet dimensions : 95.0 x 80.0 x 120.0

Standard number of units per pallet : 96

Net weight (kg) : 0.594

Gross weight (kg) : 0.8

EAN code : 4242003878279



4 242003 878279

installation accessory
HZ9VRUD0

Features

- # Mandatory installation accessory for unducted recirculation configurations. Recommended for recirculation against an internal wall or island bench. Includes:
 - 4 high-performance cleanAir odor filters with optimized odor reduction performance for cooking applications with complex odor molecules (e.g. fish). Large scale filter surfaces with high odor reduction capabilities and a lifetime of 360 hours of cooking (nonregenerative). Filters are additionally optimized for low-noise with optimized psycho-acoustics.
 - A telescopic slider element with integrated sealings and a self-gluing fixation frame to easily connect the appliance's air outlet with the cut-out in backpanel of the furniture. #This "Plug 'n Play" installation kit enables very convenient plannings and very convenient and quick installations. A return-flow aperture of $\geq 400\text{cm}^2$ is to be respected in the plinth area. This configuration requires a vertical aperture of min. 25mm behind the backpanel of the furniture. Suggested for ideal performance are 50mm. For recirculation against an external wall we recommend partly or fully ducted recirculation extraction (using Z821PD0).

installation accessory
HZ9VRUD0

Dimensioned drawings

