# BIC603S 60cm, 3 Zone Slide Control Induction Cooktop





9 stage scrolling temperature

Features

**Boost Functions** 

Overflow cut off

Locking function

99 minute Timer on all zones

## Model Code

BIC603S

# Description

60cm, 3 zone induction cooktop, slide control, no frame

# Warranty

BLANCOCare™ 2 years parts & labour

### Benefits

With 9 different settings, you can select the ideal cooking temperature for all types of foods to provide the perfect cooking

Convenient feature on 2 of the zones whereby the cooking zone selected 'boosts' to the maximum power level and will stay on

A zone that is big enough to accommodate most pots and pans and powerful enough to cook even the most heat demanding

Safety feature of the cooktop, the unit will shutdown automatically if:

- Pan is boiling over and spills into the touch controls
- A damp towel is placed over the touch controls


Pause option

Allows one to stop the cooking process at any time and to start again. A convenient and unique function.

A safety feature to help prevent children from accessing cooktop controls. User can either 'lock' the cooktop either whilst in operation or when it is off.

Each zone has its own 99 minute timer function - a convenient and easy way to program the cooking time on any cooking zone. When the timer ends a beep will sound to advise the cooking is

# Specifications



Method of installation: Benchtop

Dimensions: 580W x 510D mm Cut-out Size: 560W x 490D mm

Please allow an extra mil on all sides to cater for

screws that project out on all 4 sides

Induction Zones: 3 zones

Controls: 9 stage touch control

Connection cable length: 1.6m Power requirement: 6.4 kW

Connection: 220 - 240V - 32 amp - hard wiring required

|             | Element Ratings | Zone Diameters |  |
|-------------|-----------------|----------------|--|
| Front Left: | 2300/3000W      | 190mm          |  |
| Rear Left:  | 1400/2000W      | 160mm          |  |
| Right:      | 2300/3000W      | 250mm          |  |
|             |                 |                |  |

#### Noto

- Must leave 50mm clearance from bottom of cooktop to dividing shelf.
- Must allow a fresh air intake and an air outlet of 4mm minimum.
- Measurements are within 2/3mm factory tolerance.
- It is advisable to check dimensions of physical product before cutting out for installation.
- $^{\star}$  Due to continual product development the information provided is not final and may be subject to change