

RRP AUS \$1,019.00

Split System Reverse Cycle air conditioner featuring inverter technology, clean front with hidden display, Bio and active carbon filter, 4 way auto swing (up, down, left, right), LCD remote (2.5kW cooling - 4.0 stars MEPS2011)



Product Details

Features

Heating and cooling modes of operation
Provides year round comfort

Auto or Manual operation
Easy to set and forget or retain full user control

4 Way Air Swing - auto or manual
4 way automatic air swing for even cooling or heating

LCD backlit wireless remote control
Easy access to all functionality combined with a large easy screen backlit to be clearly readable in all lighting conditions

Fade away digital display
Display can be turned off to eliminate distraction or to darken a room for sleeping

Follow Me command
Measures and controls the temperature where you are for personal comfort

Advanced Sleep Mode
3 sleep modes to maximise comfort throughout the night and minimise energy usage

24 hour timer
Program your air conditioner to turn on and off automatically

Auto restart
In the event of an interruption in power supply the unit will restart with the same settings that were selected prior to the power outage

Inverter compressor technology
Electronic compressor control for maximum energy efficiency and minimum noise

Up to 5 year comprehensive residential warranty

Product Details

Benefits

Peace of mind

BioFresh filtration is the ideal way to purify, sterilise and deodorise the air in your living areas

Superior comfort and control

With DC inverter technology you'll enjoy greater comfort, control and energy efficiency all year round

Easy to use

One touch climate control is at your fingertips with a simple-to-use remote control

Easy to clean

The contemporary clean-face fascia not only looks good, it also minimises dust build-up on the front of the unit. Slim and compact, these air-conditioners are unobtrusive and will suit any interior style

Specifications

PRODUCT PROFILE

Domestic warranty details (yrs)	5
Type	reverse cycle

SPECIFICATIONS

Nominal horsepower	1.0
Capacity cool watts	2500
Capacity cool Btu/h	8500
Capacity Heat watts	3200
Capacity Heat Btu/h	10900
Current rating amps	10 amps
Power Supply Connection Point (for the indoor unit)	indoor unit
Service cord length	1.5
Colour of fascia	White, Digital Fade Out Display
Compressor type	rotary
Indoor sound pressure dBA high setting	43
Indoor sound pressure dBA low setting	26
Outdoor sound pressure dBA	52
Indoor air circulation max (ltr/s)	200
Ambient temperature range minimum	-15
Ambient temperature range maximum	48
Moisture removal ltr/hour	0.8
New Energy star rating cooling	4.0
New Energy star rating heating	4.0
Cooling EER	4.39
Heating COP	4.39

Specifications

Refrigerant weight (g)	1080
Refrigerant type	R410A

INDOOR UNIT DIMENSIONS

Total width (mm)	896
Total height (mm)	316
Total depth (mm)	205
Refrigerant weight (g)	1080
Refrigerant type	R410A

OUTDOOR UNIT DIMENSIONS

Width (mm)	848
Height (mm)	540
Depth (mm)	320
Refrigerant weight (g)	1080
Refrigerant type	R410A

FEATURES

Filtration	dust,hepa,carbon,plasma
Remote control type	back lit
Timer	24 hour
Anti corrosion treatment	Hydrophilic Blue Fin Coating - Indoor & Outdoor Units
Fan speeds	low,medium,high,turbo,Medium-low,Medium-high,Auto
Refrigerant weight (g)	1080
Refrigerant type	R410A

INSTALLATION REQUIREMENTS (PIPING AND WIRING)

Gas pipe size	9.52
Liquid pipe size	6.35
Maximum piping length vertical	10
Maximum piping length horizontal	15
Maximum pipe length with supplied charge	7.5
Wires connecting indoor unit to outdoor unit	4
Refrigerant weight (g)	1080
Refrigerant type	R410A

OUTDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.183
Shipping Weight (Kg)	34.5
Pack Dimensions Width (mm)	878
Pack Dimension Height (mm)	580
Pack Dimension Depth (mm)	360
Refrigerant weight (g)	1080
Refrigerant type	R410A

INDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.102
Shipping Weight (Kg)	13.5
Pack Dimensions Width (mm)	950
Pack Dimension Height (mm)	385
Pack Dimension Depth (mm)	280
Refrigerant weight (g)	1080
Refrigerant type	R410A

STUFFING QUANTITIES

20ft	90
40ft	184
40ft HC	219
Refrigerant weight (g)	1080
Refrigerant type	R410A

Terms and Conditions

IMPORTANT

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

PRODUCT INFORMATION

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous product development, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes the products that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products Pty Ltd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours of products illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

ELECTROLUX HOME PRODUCTS AUSTRALIA

telephone: 1300 363 640

fax: 1800 350 067

email: customercare@electrolux.com.au

web: www.electrolux.com.au

ELECTROLUX HOME PRODUCTS NEW ZEALAND

telephone: 09 573 2230

fax: 09 573 2221

email: customercare@electrolux.co.nz

web: www.electrolux.co.nz