

RRP AUS \$1,009.00

Split System Reverse Cycle air conditioner featuring inverter technology, clean front with LED display, Bio and active carbon filter, 2 way auto swing (up, down), remote (3.5kW cooling - 2.5 stars MEPS2011)



Product Details

Features

Heating and cooling modes of operation
Provides year round comfort

Auto or Manual operation
Easy to set and forget or retain full user control

Auto air swing
Air can be automatically be directed up and down to distribute cooling or heating evenly

LCD backlit wireless remote control
Easy access to all functionality combined with a large easy screen backlit to be clearly readable in all lighting conditions

Follow Me command
Measures and controls the temperature where you are for personal comfort

Sleep mode
Sleep mode automatically adjusts the temperature while you sleep for maximum comfort and minimum energy consumption

24 hour timer
Program your air conditioner to turn on and off automatically

Auto restart
In the event of an interruption in power supply the unit will restart with the same settings that were selected prior to the power outage

Inverter compressor technology
Electronic compressor control for maximum energy efficiency and minimum noise

Up to 5 year comprehensive residential warranty

Product Details

Benefits

Peace of mind

BioFresh filtration is the ideal way to purify, sterilise and deodorise the air in your living areas

Superior comfort and control

With DC inverter technology you'll enjoy greater comfort, control and energy efficiency all year round

Easy to use

One touch climate control is at your fingertips with a simple-to-use remote control

Easy to clean

The contemporary clean-face fascia not only looks good, it also minimises dust build-up on the front of the unit. Slim and compact, these air-conditioners are unobtrusive and will suit any interior style

Specifications

PRODUCT PROFILE

Domestic warranty details (yrs)	5
Type	reverse cycle

SPECIFICATIONS

Nominal horsepower	1.5
Capacity cool watts	3450
Capacity cool Btu/h	11800
Capacity Heat watts	3600
Capacity Heat Btu/h	12300
Current rating amps	10 amps
Power Supply Connection Point (for the indoor unit)	indoor unit
Service cord length	1.5
Colour of fascia	White, Digital Display
Compressor type	rotary
Indoor sound pressure dBA high setting	43
Indoor sound pressure dBA low setting	28
Outdoor sound pressure dBA	52
Indoor air circulation max (ltr/s)	153
Ambient temperature range minimum	-7
Ambient temperature range maximum	48
Moisture removal ltr/hour	1.4
New Energy star rating cooling	2.5
New Energy star rating heating	2.5
Cooling EER	3.71
Heating COP	3.75

Specifications

Refrigerant weight (g)	970
Refrigerant type	R32

INDOOR UNIT DIMENSIONS

Total width (mm)	912
Total height (mm)	290
Total depth (mm)	188
Refrigerant weight (g)	970
Refrigerant type	R32

INSTALLATION REQUIREMENTS (PIPING AND WIRING)

Gas pipe size	9.52
Liquid pipe size	6.35
Maximum piping length vertical	10
Maximum piping length horizontal	20
Maximum pipe length with supplied charge	7.5
Wires connecting indoor unit to outdoor unit	4
Refrigerant weight (g)	970

OUTDOOR UNIT DIMENSIONS

Width (mm)	842
Height (mm)	596
Depth (mm)	320
Refrigerant weight (g)	970
Refrigerant type	R32

FEATURES

Filtration	biofresh,dust,carbon,hepa
Remote control type	LCD
Timer	24 hour
Anti corrosion treatment	Hydrophilic Blue Fin Coating - Indoor & Outdoor Units
Fan speeds	low,medium,high,turbo,Auto
Refrigerant weight (g)	970
Refrigerant type	R32

INDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.090
Shipping Weight (Kg)	11.5
Pack Dimensions Width (mm)	984
Pack Dimension Height (mm)	354
Pack Dimension Depth (mm)	257
Refrigerant weight (g)	970
Refrigerant type	R32

OUTDOOR UNIT PACKED DIMENSIONS

Shipping Volume (m3)	0.199
Shipping Weight (Kg)	38.5
Pack Dimensions Width (mm)	878
Pack Dimension Height (mm)	630
Pack Dimension Depth (mm)	360
Refrigerant weight (g)	970
Refrigerant type	R32

STUFFING QUANTITIES

20ft	81
40ft	180
40ft HC	204
Refrigerant weight (g)	970
Refrigerant type	R32

Terms and Conditions

IMPORTANT

This is a guide of product dimensions only. For complete installation instructions, refer to the manual provided with product.

PRODUCT INFORMATION

The descriptors and illustrations in this publication apply to the specific products and models described as at the date of issue. Under our policy of continuous product development, product specifications may change without notice. Prospective purchasers should therefore check with their retailer to ensure this publication correctly describes the products that are being offered for sale. All information supplied is to be used for general reference purposes only and is on the understanding that Electrolux Home Products Pty Ltd (Australia) and Electrolux (NZ) Ltd (New Zealand) will not be liable for any loss, liability or damage of whatever kind arising as a result of reliance on such information. Colours of products illustrated are as close as printing limitations allow. Electrolux will at all times comply with its obligations pursuant to law including Trade Practices (Australian Consumer Law) Act and Regulations.

WARRANTY

This warranty only applies to Appliances purchased and used in Australia or New Zealand and used in normal domestic applications and is in addition to (and does not exclude, restrict, or modify in any way) any non-excludable statutory warranties in Australia or New Zealand. All warranties are subject to the conditions set out in the warranty card accompanying the product when purchased.

ELECTROLUX HOME PRODUCTS AUSTRALIA

telephone: 1300 363 640

fax: 1800 350 067

email: customercare@electrolux.com.au

web: www.electrolux.com.au

ELECTROLUX HOME PRODUCTS NEW ZEALAND

telephone: 09 573 2230

fax: 09 573 2221

email: customercare@electrolux.co.nz

web: www.electrolux.co.nz